



LACNAM PAINTS AUSTRALIA

ABN 48 125 092 482

78-80 MANDOON, ROAD, GIRRAWEE, SYDNEY

NSW 2145 AUSTRALIA

TELEPHONE: (02) 9688 1999 FACSIMILE: (02) 9896 1606

EMAIL: [sales@lacnam.com.au](mailto:sales@lacnam.com.au) WEBSITE: [www.lacnam.com.au](http://www.lacnam.com.au)

## TECHNICAL INFORMATION SHEET

March 2009

TDS 291 page 1 of 2

# 291 WOOD PRIMER

### Description and uses:

291 Wood Primer is a high quality linseed based primer for timber which is to be topcoated with finishes suitable for application over a linseed oil or alkyd based primer.

291 Wood Primer is formulated for use with commercial machinery designed to coat fascia boards and other pre-primed timber for the building industry.

### Technical Specifications:

FINISH: Flat Pink or Cream.

THINNERS: T195.

VOLUME SOLIDS: 45 - 48%.

VOC: 420gms/litre.

COVERAGE: 10 - 12 Square metres per litre (at a D.F.T. of 45 microns).

RECOMMENDED FILM THICKNESS: 40 - 60 microns.

APPLICATION: Mechanical Applicator.

DRYING AT 25°C / 50% Humidity: Touch dry: 4 - 6 hours.

**Surface Preparation:** All surfaces should be sanded if necessary and dusted before painting. Do not apply at temperatures below 5' Celsius. Do not apply at relative humidity above 85%, or when the substrate surface is less than 3' Celsius above dewpoint.

**Application Details:** Can be brushed or rolled as is or with up to 5% thinner addition. Machine coating - use as per manufactures directions.

# 291 WOOD PRIMER

March 2009

TDS 291 page 2 of 2

## **Safety Instructions:**

Storage: Store in a cool, dry banded area out of direct sunlight as required for Flammable liquids DG Class 3, PG II, Hazchem 3(Y)E.

Flammability: Highly flammable, all sources of ignition must be eliminated in or near area of use, on burning fumes emitted are toxic. Do not smoke in immediate area.

Handling: Adopt adequate Occupational Work Practices to avoid personal contamination with product. Always wash hands before smoking, eating, drinking or using toilet. Food and Drink should be to stored and consumed in separate area.

Personal Protection: Avoid contact with skin or eyes; wear suitable clothing such as impervious overalls, PVC or neoprene gloves, safety goggles and face mask.

Using: Avoid inhalation of spray mist and vapours – use with adequate ventilation and suitable Personal Protection Equipment (PPE).

Engineering controls: Ensure ventilation is adequate. When spraying, ensure product is applied in a fully functional spray-booth. Keep containers closed when not in use. Do not use near ignition sources.

## **REFER MSDS BEFORE USE**

(Phone 02 9688 1999 or refer to [www.lacnam.com.au](http://www.lacnam.com.au) for copy MSDS)

Although this information is presented in good faith and compiled from sources believed to be accurate, Lacnam Paints make no representations or warranty as to the completeness or accuracy thereof. As the product's performance and suitability depends on various factors, the purchasers of our products should determine for themselves whether the product is suitable for their particular use.