

**SAFETY DATA SHEET****1. IDENTIFICATION OF MATERIAL & COMPANY DETAILS**

**Product Name:** T170 ACRYLIC LACQUER THINNER  
**Product description:** Solvent Mixture  
**Recommended Use:** Industrail solvent for paint thinning and clean up.  
**CAS Number:** Not Applicable  
**Company Name:** Lacnam Paints Australia  
**Address:** 78-80 Mandoon Road, Girraween, NSW 2145  
**Email:** sales@lacnam.com.au  
**Telephone Number:** (02) 9688-1999  
**Facsimile:** (02) 9896 1606  
**Emergency Number:** (02) 9636-5505 (after hours)

**2. HAZARDS IDENTIFICATION****HAZARDOUS SUBSTANCE-DANGEROUS GOODS:**

Classified as hazardous according to criteria of Work Safe Australia

Classified as dangerous according to Dangerous Good Code

**Signal Word:** DANGER**GHS Classification:**

Flammable Liquid: Category 2

Aspiration hazard: Category 1

Eye Irritation Hazard: Category 2A

Skin irritation: Category 2

Carcinogenicity: Category 2

Hazardous to the Aquatic Environment - Long-Term Hazard: Category 2

Acute Aquatic Toxicity: Category 2

Chronic Aquatic Toxicity: Category 2

Specific Target Organ Toxicity (central nervous system): Category 3

Specific Target Organ Toxicity-Single Exposure (Narcotic effect): Category 2

Specific Target Organ Toxicity-Repeated Exposure: Category 2

Toxic to Reproduction: Category 1A

**Hazard Statements:**

H225 - Highly flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H336 - May cause drowsiness and dizziness

H351 - Suspected of causing cancer

H360 - May damage fertility or the unborn child.

H373 - May cause damage to organs through prolonged or repeated exposure .

H410 - Very toxic to aquatic life with long lasting effects

**Non GHS Hazard Statement:**

AUH066 - Repeated exposure may cause skin dryness and cracking

## SAFETY DATA SHEET

Name: T170 Acrylic Lacquer Thinner

Page 2 of 11

Date of Issue: 01/10/2016

### 2. HAZARDS IDENTIFICATION

#### Prevention Precautionary Statements:

- P101 - If medical advice is needed, have product container or label at hand
- P102 - Keep out of reach of children
- P103 - Read label before use
  
- P202 - Do not handle until all safety precautions have been read and understood
- P210 - Keep away from heat/sparks/open flames/hot surfaces – No smoking
- P233+234 - Keep container tightly closed. Keep only in original container
- P240 - Ground/bond container and receiving equipment.
- P241 - Use explosion-proof electrical/ventilating/light/.../equipment
- P242+243 - Use only non-sparking tools. Take precautionary measures against static discharge
- P261 - Avoid breathing dust/fume/gas/mist/vapours/spray
- P262 - Do not get in eyes, on skin, or on clothing
- P264 - Wash all exposed skin area thoroughly after handling
- P270 - Do not eat, drink or smoke when using this product
- P272 - Contaminated work clothing should not be allowed out of the workplace
- P273 - Avoid release to the environment
- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P285 - In case of inadequate ventilation wear respiratory protection

#### Response Precautionary Statements:

- P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
- P302+352 - IF ON SKIN: Wash with soap and water
- P303+361+353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
- P306+360 - IF ON CLOTHING: Rinse immediately contaminated clothing and skin with plenty of water before removing clothes
- P312 - Call a POISON CENTRE or doctor/physician if you feel unwell.
- P321 - Specific treatment: Immediate First Aid Measures Refer Section 4 of Safety Data Sheet
- P333+313 - If skin irritation or a rash occurs: Get medical advice/attention
- P337+313 - If eye irritation persists get medical advice/attention
- P363 - Wash contaminated clothing before reuse
- P370+P378 - In case of fire: Use Foam, Dry Chemical Powder, Carbon Dioxide, Fine Water Spray or Fog (for large fires only) for extinction
- P391 - Collect spillage

#### Storage Precautionary Statements:

- P403+233+235: Store in a well ventilated place. Keep container tightly closed. Keep cool
- P405 - Store locked up

#### Disposal precautionary statements:

- P501: Dispose of contents/container in accordance with local, regional, national and international regulations.

**Poison Schedule:** S5.Caution

## SAFETY DATA SHEET

Name: T170 Acrylic Lacquer Thinner

Page: 3 of 11

Date of Issue: 01/10/2016

### 3. COMPOSITION/INFORMATION OF INGREDIENTS

Component Name:	CAS Number:	Proportion % Weight:
Solvent naphtha (petroleum), light aromatic	64742-95-6	45.0 - 65.0
Propanone	67-64-1	15.0 - 25.0
2-Methoxy-1-methylethyl acetate	108-65-6	05.0 - 15.0
Methyl ethyl ketone	78-93-3	05.0 - 15.0
Ethyl alcohol	64-17-5	01.0 - 10.0

### 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

#### Inhalation:

- Remove victim from exposure-avoid becoming a casualty. Remove all contaminated clothing and footwear.
- Allow patient to assume most comfortable position and keep warm.
- If inhalation of mists, fumes or vapour causes irritation to the nose, throat or lungs, causing coughing, wheezing or impaired motor skills, remove patient to fresh air.
- If symptoms persist, obtain medical advice.

#### Skin:

- Remove all contaminated clothing and footwear.
- Wash contaminated area thoroughly with soap and water as soon as reasonably practicable.
- For gross contamination immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble).
- For skin burns cover with a clean dry dressing, if blistering occurs do not break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

#### Eyes:

- Immediately flush eyes with large amounts of water for at least 15 minutes.
- Method of irrigation; keep eyelids apart and away from eyes, routinely lift upper and lower eyelid away from eye while flushing with water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes.
- Removal of contact lenses should only be performed by skilled personnel.
- Transport to the nearest medical facility for additional treatment.

#### Swallowed:

- Do not induce vomiting, place person's face downwards, head lower than hips to prevent vomit entering lungs.
- Rinse mouth with water. Give water to drink.
- Avoid giving patient milk or oils.
- Observe patient carefully; withhold water if patient display signs of drowsiness or reduced awareness and possible unconsciousness.
- Seek medical advice.

#### First Aid Facilities:

- Ensure that eye wash bath and safety showers are readily accessible.

#### Advice to Doctor:

- Treat the patient symptomatically.

For acute or short term repeated exposure to petroleum distillates or related hydrocarbons the primary threat to life is respiratory failure from ingestion and/or inhalation. Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostals retraction, or obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> 50 mm Hg) should be intubated.

## SAFETY DATA SHEET

Name: T170 Acrylic Lacquer Thinner

Page 4 of 11

Date of Issue: 01/10/2016

### 5. FIRE FIGHTING MEASURES

**Hazchem Code: 3YE**

#### **Fire & Explosion Hazard:**

- Liquid and vapours are highly flammable.
- Explosion hazard when exposed to heat or flame.
- Vapour may travel a considerable distance to source of ignition.
- Containers may rupture violently when exposed to extreme heat.
- On combustion the following products may be produced; Carbon Dioxide, Carbon Monoxide, Soot and Toxic smoke.
- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

#### **Fire Fighting:**

- Evacuate immediate area of non-emergency personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Wear full protective equipment including self-contained breathing apparatus.
- Fight fire from a safe distance, with adequate cover and safe fire escape exit.
- Use foam, dry chemical or carbon dioxide extinguishers. Fine water spray may be used to cool containers to prevent vapour pressure build up.
- Prevent water runoff from entering storm water drains or waterways.

### 6. ACCIDENTAL RELEASE MEASURES

#### **Minor Spills:**

- Clean up all spills immediately.
- Eliminate all sources of ignition
- Wear full protective clothing (refer section 8)
- Avoid breathing vapours and contact with skin and eyes.
- Contain and absorb using earth, sand, vermiculite or other absorbent material. DO NOT USE sawdust, this is flammable.
- Collect residues in a flammable waste container and dispose of according to local waste management regulations.
- Do not allow product to enter storm water drains or waterways.
- Immediately remove all contaminated clothing after containment.

#### **Major Spills:**

- Evacuate personnel from immediate area and move upwind.
- Alert Fire Brigade of location and nature of hazard
- Eliminate all sources of ignition
- Wear full protective clothing (refer section 8)
- If safe to do so eliminate source of spillage.
- Avoid breathing vapours and contact with skin and eyes.
- Prevent, by any means available, spillage from entering storm water drains or water ways.
- If possible contain and absorb using earth, sand, vermiculite or other absorbent material. DO NOT USE sawdust, this is flammable.
- Use only anti-spark/ anti-static equipment to contain and remove spillage.
- Recoverable product should be collected into labeled flammable containers for recycling.
- Collect residues in a flammable waste container and dispose of according to local waste management regulations.
- Immediately remove all contaminated clothing after containment.

## SAFETY DATA SHEET

Name: T170 Acrylic Lacquer Thinner

Page 5 of 11

Date of Issue: 01/10/2016

<b>7. HANDLING AND STORAGE</b>
--------------------------------

**Safe Storage:**

- Store product in accordance with Local State, or Territory Dangerous Goods Regulations.
- Keep containers closed when not in use.
- Store in a cool, dry, well-ventilated area out of direct sunlight, away from sources of heat or ignition.
- Do store in areas where vapours may be concentrated i.e. pits, basements, or unventilated storage area.
- Do not store or load on the same vehicle as Class 1, Class 2.1, Class 2.3, Class 4.2, Class 5.1, Class 5.2 or Class 7 materials.

**Precautions for safe handling:**

- Do not smoke in storage/work area.
- Avoid skin and eye contact and breathing in vapour.
- All material handling equipment in work area must be flameproof.
- All nearby equipment should be earthed
- All potential sources of ignition must be eliminated from storage/work area.

<b>8. EXPOSURE CONTROLS AND PERSONAL PROTECTION</b>
---

**Occupational Exposure Limits:** No value assigned for this specific product by Safe Work Australia: Hazardous Substances Information System (HSIS).

**Concentration Cut-off Levels:**

A concentration cut-off level for a substance is the level (expressed as a percentage on a weight/weight basis for solids and liquids and a volume/volume basis for gases) at and above which that substance is classified as a hazardous substance. A mixture is classified as a hazardous substance if it contains at least one ingredient at a concentration equal to, or above, the lowest concentration cut-off level given for that ingredient. Concentration cut-off levels refer to health hazards only, and are not associated with the physicochemical or environmental hazards of a substance. The health effects of certain types of hazardous substances are regarded as additive. Due to additive effects, a mixture may be classified as hazardous even if all of the individual substances in the mixture are present at levels below their respective cut offs.

- Reportable exposure limits for individual components that exceed **Concentration Cut Off levels:**

Chemical Name	CAS. No	TWA (8hr)		STEL		Source	Notices	%weight
		ppm	mg/m3	ppm	mg/m3			
• Solvent naphtha (petroleum), light aromatic	64742-95-6	Not assigned						<45.00
• Methyl benzol	108-88-3	50	191	150	574		Sk	<35.00
Propanone	67-64-1	500	1185	1000	2375	N/Eu;A		
2-Methoxy-1-methylethyl acetate	108-65-6	50	274	100	548	N/Eu;A	Sk	<15.00
Methyl ethyl ketone	78-93-3	150	445	300	890		Eu;A	<15.00
Ethyl alcohol	64-17-5	1000	1880			N/Eu, A		<10.00

**Source:**

- A Listed in the National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC: 1003(1995).
- Eu Listed in the European Union's Annex I of the EEC Council Directive 67/548/EEC (as updated by EEC Council Directive 2001/59/EC).
- NIOSH National Institute for Occupational Safety and Health.
- NZWS New Zealand Workplace Exposure Standards and Biological Exposure Indices 7th edition
- Sk Absorption through the skin may be a significant source of exposure.
- (a) The value for inhalable dust containing no asbestos and less than 1.0% free silica.
- ACGIH American Conference of Governmental Industrial Hygienists

## SAFETY DATA SHEET

Name: T170 Acrylic Lacquer Thinner  
Page 6 of 11  
Date of Issue: 01/10/2016

<b>8. EXPOSURE CONTROLS AND PERSONAL PROTECTION</b>
---

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable.

Exposed individuals may be desensitised to product and are not reasonably expected to be warned, by smell, that exposure standard is being exceeded.

If the TWA concentration of ANY of the components is exceeded the individual is deemed to be over exposed.

If the directions for use on the Product Label/Safety Data Sheet are followed, exposure using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:  
Biological Exposure Index (BEI):**

Material name	Determinant	Determinant	BEI	Reference
Methyl benzol	Methylhippuric acids in urine	End of shift	1.6 g/g creatine	ACGIH (2003)
	o-cresol in urine	End of shift	0.5mg/l	ACGIH (2003)
	Toluene in Blood	Prior to last shift of work week	0.02mg/l	ACGIH BEL(01 2010)
	o-Cresol, with hydrolysis	End of shift	0.3mg/g	ACGIH BEL(01 2010)
	Creatinine in urine	End of shift	0.03mg/l	ACGIH BEL(01 2010)
	Toluene in urine			

**Engineering Controls:** Use process enclosures, local exhaust ventilation or other engineering controls to maintain worker exposure to airborne contaminants below any recommended or statutory limits. Keep containers closed when not in use. Ensure exhaust air does not contaminate other work spaces.  
Vapour heavier than air - Prevent vapours concentrating in work pits, tanks or sumps. DO NOT enter confined spaces where vapour may have collected.  
Ensure electrical equipment is in accordance with applicable regulations.  
Equipment used to transfer product should be adequately earthed.  
Ventilation equipment should be explosion/flame resistant.  
Do not use near ignition sources.

**Personal Protection:** Avoid contact with skin and eyes. Wear suitable clothing such as impervious overalls, PVC, or Neoprene gloves, and safety goggles. Where workplace ventilation is assessed as inadequate and vapours/mists are generated, the use of an approved Half or Full Face Respirator with Type A-P Filter complying with Australian Standards AS1715/1716 is recommended. Select a filter suitable for organic gases and vapours rated for; [boiling point < 65°C]. If working in confined spaces with inadequate ventilation, wear an air-fed full face mask.



**Confined Space Application:**



**Flammability:** Highly flammable. Avoid heat and sources of ignition. Container should be earthed when pouring.

## SAFETY DATA SHEET

Name: T170 Acrylic Lacquer Thinner  
Page 7 of 11  
Date of Issue: 01/10/2016

<b>9. PHYSICAL AND CHEMICAL PROPERTIES:</b>
---

**Appearance:** Colourless Liquid.  
**Odour:** Aromatic  
**Boiling Range:** 56  
**Flash point:** -18.0  
**Explosion/Flammability Limits (% by Volume):** Not available  
**Auto-ignition temperature (°C):** Theoretical 315  
**Specific Gravity:** 0.812  
**Solubility in Water:** Below 0.1% Mass  
**Decomposition Temp:** Stable under normal condition of use.

<b>10. STABILITY AND REACTIVITY:</b>
--------------------------------------

**Chemical stability:** Stable under normal conditions of use.

**Do not store:** In areas of extreme heat generated by naked flame or heating element.  
In the presence of incompatible materials. Refer Section 7.

**Incompatible materials:** Do not stow with Reactive or oxidizing agents.

**Hazardous combustion:** Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

<b>11. TOXICOLOGICAL INFORMATION:</b>
---------------------------------------

No value has been assigned for T170 Acrylic Lacquer Thinner. No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product Label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are.

**Acute Toxicity: Refer Table 1 Section 16:**

Chemical Name	Cas. No	Result	Species	Dose	Exposure
Methyl ethyl ketone	78-93-3	LD50 Oral LD50 Dermal	Rat Rabbit	2737mg/kg 6480mg/kg	
Solvent naphtha (petroleum), light aromatic	64742-95-6	LD50 Oral LD50 Dermal LC50 Inhalation	Rat Rabbit Rat	>2000mg/kg >2000mg/kg >20mg/l	4 hours
2-Methoxy-1-methylethyl acetate	108-65-6	LD50 Oral LD50 Dermal LC50 Inhalation	Rat Rabbit Rat	6190mg/kg >5000mg/kg 4345ppm	6 hours
Propanone	67-64-1	LD50 Oral LD50 Dermal LC50 Inhalation	Rat Guinea pig Rat	580mg/kg 50100mg/kg 7426mg/l	8 hours
Ethyl alcohol	64-17-5	LD50 Oral	Rat	>2000mg/l	

**Routes of exposure:** Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

**Skin irritation:** Irritating to skin. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.

**Serious eye damage/ irritation:** Moderately irritating to eye.

**Respiratory Irritation:** Inhalation of vapors or mists may cause irritation to the respiratory system.

## SAFETY DATA SHEET

Name: T170 Acrylic Lacquer Thinner  
Page: 8 of 11  
Date of Issue: 01/10/2016

<b>11. TOXICOLOGICAL INFORMATION:</b>
---------------------------------------

<b>Sensitization:</b>	Not a skin sensitiser
<b>Aspiration Hazard:</b>	Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
<b>Germ cell mutagenicity:</b>	Not mutagenic.
<b>Carcinogenicity:</b>	Limited evidence of carcinogenic effect. (Naphthalene).
<b>Reproductive and</b>	Not expected to impair fertility.
<b>Developmental toxicity:</b>	Causes foetotoxicity in animals at doses which are maternally toxic.
<b>Specific target organ toxicity-single exposure:</b>	May cause drowsiness or dizziness

<b>12. ECOLOGICAL INFORMATION:</b>
------------------------------------

No value has been assigned for T170 Acrylic Lacquer Thinner. Avoid contaminating waterways.

**Acute Aquatic Ecotoxicity**

Chemical Name	Cas.No	Species	Result	Method	Exposure
2-Methoxy-1-methylethyl acetate	108-65-6	Fish (Fathead minnow)	LC50 - 161mg/l		96 hours
		Aquatic Crustacea (Water flea)	LC50 - 408mg/l		48 hours
Propanone	67-64-1	Aquatic Crustacea (Water flea)	EC50 - 13500mg/l		48 hours
Methyl ethyl ketone	78-93-3	Fish (Fathead minnow)	LC50 - 3130-3320mg/l		96 hours
		Aquatic Crustacea (Water flea)	LC50 - >520mg/l		48 hours
			EC50 - 7060mg/l		24 hours
Methyl benzol	108-88-3	Fish	1<LC/EC/IC50<=10mg/L		
		Aquatic Invertebrates	10<LC/EC/IC50<=100mg/L		
		Algae	Practically non-toxic LC/EC/IC50<=10mg/L		
Solvent naphtha (petroleum), light aromatic	64742-95-6	Fish	1<LC/EC/IC50<=10mg/L		
		Aquatic Invertebrates	1<LC/EC/IC50<=10mg/L		
		Algae	1<LC/EC/IC50<=10mg/L		
		Microorganisms	LC/EC/IC50>100mg/L expected low toxicity		
Ethyl alcohol	64-17-5	Fish	LL/EL/IL50 > 100 mg/l		
		Aquatic Crustacea	LL/EL/IL50 > 100 mg/l		
		Algae/Aquatic Plants	LL/EL/IL50 > 100 mg/l		
		Microorganisms	LL/EL/IL50 > 100 mg/l		
			Practically non-toxic:		

**Chronic Aquatic Ecotoxicity:**

2-Methoxy-1-methylethyl acetate	108-65-6	Fish (Oryzias latipes)	LC50 - 63.5mg/l		14 days
		Aquatic Crustacea (Water flea)	NOEC - 47.5mg/l		14 days
		Algae (Selenastrum capricornutum)	NOEC: >= 100 mg/l		21 days
			EC - 50: > 100 mg/l		21 days
			NOEC: >= 1000 mg/l		96 hours
Methyl ethyl ketone	78-93-3	Fish (sheepshead minnow)	mortality NOEC - 400mg/l		96 hours
Methyl benzol	108-88-3	Fish	NOEC/NOEL expected to be >0.1 - <=1.0 mg/l (based on modeled data)		
		Aquatic Invertebrates	NOEC/NOEL expected to be >0.1 - <=1.0 mg/l (based on modeled data)		
Ethyl alcohol	64-17-5	Fish	NOEC/NOEL expected to be > 100 mg/l (based on modeled data)		
		Aquatic Invertebrates	NOEC/NOEL > 1.0 - <=10 mg/l		



## SAFETY DATA SHEET

Name: T170 Acrylic Lacquer Thinner  
Page: 9 of 11  
Date of Issue: 01/10/2016

### 12. ECOLOGICAL INFORMATION:

**Persistence and Biodegradability:** Readily biodegradable. Oxidises rapidly by photo-chemical reactions in air.

**Mobility in Soil:** Floats on water. If product enters soil, it will be highly mobile and may contaminate groundwater.

**Bioaccumulative Potential:** Product does not bioaccumulate significantly.

### 13. DISPOSAL CONSIDERATION:

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is use, See "Section 8. Exposure Controls and Personal Protection" of the SDS.

**Material Disposal:** Recover or recycle if possible. It is the responsibility of waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

**Container Disposal:** Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Refer to Section 7 before handling the product or containers. Residues may cause an explosion hazard if heat above flash point. Do not puncture, cut or weld uncleaned drums. Send to drum or metal recyclers.

**Local Legislation:** Disposal should be in accordance with applicable regional, nation, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

### 14. TRANSPORT INFORMATION:

Classified as Dangerous Goods by criteria of the Australian Dangerous Goods Code (ADG Code) for transport by road or rail.



**Product Name:** T170 Acrylic Lacquer Thinner

**Other Names:** Paint Thinner

**Manufacturer's Product Code:** T170

**UN Number:** 1263

**Packaging Group:** II

**Dangerous Goods Class & Subsidiary Risk:** 3

**Hazchem Code:** +3YE

**Limited Quantity:** 5 litres

**Declaration for land shipment:** PAINT RELATED MATERIAL (including paint thinning or reducing compound)

#### Air Transport IATA:

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA), Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

**Product Name:** T170 Acrylic Lacquer Thinner

**ICAO/IATA Class:** 3

**Subsidiary risk:** None

**UN No:** 1263

**Packaging Group:** II

**Shipping name:** PAINT RELATED MATERIAL (including paint thinning or reducing compound)

#### Marine Transport:

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

**Product Name:** T170 Acrylic Lacquer Thinner

**UN No:** 1263

**Class-primary:** 3

**Packing Group:** II

**IMDG Marine Pollutant:** Yes (Naphthalene)

**Shipping Name:** PAINT RELATED MATERIAL (including paint thinning or reducing compound)

## SAFETY DATA SHEET

Name: T170 Acrylic Lacquer Thinner

Page: 10 of 11

Date of Issue: 01/10/2016

### 14. TRANSPORT INFORMATION:

Do not load on the same vehicle as:

- Class 1: Explosives
- Class 2.1: Flammable Gases
- Class 2.3: Toxic Gasses
- Class 4.2: Spontaneously Combustible Substances
- Class 5.1: Oxidising Agents
- Class 5.2: Organic Peroxides
- Class 7: Radioactive Substances

### 15. REGULATORY INFORMATION

**Poison Schedule:** S5

#### Individual components of T170 Acrylic Lacquer Thinner on regulatory listings:

Solvent naphtha (petroleum), light aromatic: **CAS No: 64742-95-6:** HVICL, AICS, ICCA, (OECD), HPV, KECI, INV (CN).

Methyl benzol: **CAS No: 108-88-3:** AICS, DSL, ENCS, TSCA, EINECS, KECI, PICCS, IVN (CN), IRAC.

2-Methoxy-1-methylethyl acetate: **CAS No: 108-65-6:** ACIS, NICNAS, DSL, TSCA, MITI, KECL, PICCS, IECSC.

Methyl ethyl ketone: **CAS No: 78-93-3:** AICS, NZIoC, DSL, ENCS, IECSC, ISHL, KECI, PICCS.

Ethyl alcohol: **CAS No: 64-17-5:** AICS, NZIoC, DSL, ENCS, IECSC, ISHL, KECI, PICCS.

Propanone: **CAS No: 67-64-1:** AICS, NZIoC, DSL, ENCS, IECSC, ISHL, KECI, PICCS.

#### REGULATORY LISTINGS:

**SUSDP:** Standard for the Uniform Scheduling of Drugs and Poisons

**HSIS:** Safe work Australia Hazardous Substances Information System

**NPI:** The National Pollutant Inventory

**OECD:** Organisation for Economic Co-operation and Development.

**AICS:** Australian Inventory of Chemical Substances

**EINECS:** European Inventory of Existing Commercial Chemical Substances

**TSCA:** US Toxic Substances Control Act

**DSL:** Canadian Domestic Substances List.

**IRAC:** International Agency for Research on Cancer

**PICCS:** Philippines Inventory of Chemicals and Chemical Substances

**KECL:** Korea Existing Chemicals List

**ENCS:** Japan Existing and New Chemical Substances

**REACH:** Registration, Evaluation, Authorisation and Restriction of Chemicals

**DSL/NDL:** Canadian Domestic Substances List/Non-Domestic Substance List

**NZIoC:** New Zealand Inventory of Chemicals

**IECSC:** Chinese Chemical Inventory of Existing Chemical Substances

**KECI:** Korea Existing Chemicals Inventory

**HSNO:** New Zealand Hazardous Substances and New Organisms Act

**ISHL:** Japan Industrial Safety and Health Law

**NICNAS:** National Industrial Chemicals Notification and Assessment Scheme

**MITI:** Japanese Handbook of Existing and New Chemical Substances

**IVN (CN):**

#### IRAC GROUP CLASSIFICATION:

Group 1 Carcinogenic to humans:

Group 2A Probably carcinogenic to humans:

Group 2B Possibly carcinogenic to humans:

Group 3 Not classifiable as to its carcinogenicity to humans: CAS No: 108-88-3

Group 4 Probably not carcinogenic to humans:

## SAFETY DATA SHEET

Name: T170 Acrylic Lacquer Thinner  
Page: 11 of 11  
Date of Issue: 01/10/2016

### 16. OTHER INFORMATION:

**CAS No:** CAS Registry Number is a unique numeric identifier that designates only one substance. It has no chemical significance.

**TWA:** Exposure standard-time weighted average; the average airborne concentration of a particle substance when calculated over a normal eight hour working day, for a five day week.

**STEL:** Short-term exposure limit (STEL) is the acceptable exposure limit to a toxic or an irritant substance over a short period of time (time-weighted average), usually 15 minutes. STEL is the maximum concentration of a chemical to which workers may be exposed continuously for a short period of time without any danger to health, safety or work efficiency.

**ppm:** Parts of vapour or gas per million parts of contaminated air by volume.

**mg/m<sup>3</sup>:** Milligrams of substance per cubic metre of air at 25°C and one atmosphere pressure. When entry is in this column only the value is exact; when listed with a ppm value, it is approximate.

**LD50:** Lethal Dosage represents the individual dose required to kill 50 percent of a population of test animals.

**LC50:** Lethal Concentrations of the chemical in air that kills 50% of the test animals during the observation period of time (traditional 4 hours). It can also mean the concentration of a chemical in water.

**EC50:** The Median Effective Concentration is the statistically derived concentration of a substance in an environmental medium expected to produce a certain effect in 50% of test organisms in a given population under a defined set of conditions.

**IC50:** Half Maximal Inhibitory Concentration is a measure of the effectiveness of a substance in inhibiting a specific biological or biochemical function. This quantitative measure indicates how much of a particular drug or other substance is needed to inhibit a given biological process (or component of a process, i.e. an enzyme, cell, cell receptor or microorganism) by half.

**LDL0:** Lethal Dose Low, lowest dose of a substance reported to have caused death in humans or animals.

**NOEC/NOEL:** No Observed Effect Concentration/ No Observable Effect Level

**MSDS Effective Date:** 01/10/2016

**MSDS Distribution:** The information in this document should be made available to all who may handle the product.

### CONTACT POINT

<b>Technical Manager</b>	- Working hours	(02) 9688-1999
	- After hours	(02) 9636-5505

Although this information is presented in good faith and compiled from various sources believed to be accurate, Lacnam Paints make no representations or warranty as to the completeness or accuracy thereof. As the product's performance and suitability depends on various factors, the purchasers of our products should determine for themselves whether the product is suitable for their particular use.

**Hazardous according to criteria of Australian Safety Compensation Council**