

**SAFETY DATA SHEET****1. IDENTIFICATION OF MATERIAL & COMPANY DETAILS**

**Product Name:** T190 GUN & BRUSH WASH

**Product description:** Solvent Mixture

**Recommended Use:** Industrail solvent for paint thinning and clean up.

**CAS Number:** Not Applicable

**Company Name:** Lacnam Paints Australia

**Address:** 78-80 Mandoon Road, Girraween, NSW 2145

**Email:** sales@lacnam.com.au

**Telephone Number:** (02) 9688-1999

**Facsimile:** (02) 9896 1606

**Emergency Number:** (02) 9636-5505 (after hours)

**2. HAZARDS IDENTIFICATION****HAZARDOUS SUBSTANCE-DANGEROUS GOODS:**

Classified as hazardous according to criteria of Work Safe Australia

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

**Signal Word: DANGER****GHS Classification:**

Aspiration Hazard: Category 1

Flammable Liquids: Category 2

Hazardous to the Aquatic Environment - Long-Term Hazard: Category 2

Skin Corrosion/Irritation: Category 2

Eye Irritation: Category 2A

STOT Repeated Exposure: Category 2

STOT Single Exposure: Category 3 (narcotic)

STOT Single Exposure: Category 3 (respiratory tract irritation)

Toxic to Reproduction: Category 1A

**Hazard Statements:**

H225 - Highly flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H336 - May cause drowsiness and dizziness

H360 - May damage fertility or the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

**Non GHS Hazard Statement:**

AUH066 - Repeated exposure may cause skin dryness and cracking

## SAFETY DATA SHEET

Name: T190 Gun & Brush Wash

Page 2 of 11

Date of Issue: 01/10/2016

### 2. HAZARDS IDENTIFICATION

#### Prevention Precautionary Statements:

- P101 - If medical advice is needed, have product container or label at hand
- P102 - Keep out of reach of children
- P103 - Read label before use
  
- P202 - Do not handle until all safety precautions have been read and understood
- P210 - Keep away from heat/sparks/open flames/hot surfaces – No smoking
- P233+234 - Keep container tightly closed. Keep only in original container
- P240 - Ground/bond container and receiving equipment.
- P241 - Use explosion-proof electrical/ventilating/light/...equipment
- P242+243 - Use only non-sparking tools. Take precautionary measures against static discharge
- P260 - Do not breathe dust/fume/gas/mist/vapours/spray
- P262 - Do not get in eyes, on skin, or on clothing
- P264 - Wash all exposed skin area thoroughly after handling
- P270 - Do not eat, drink or smoke when using this product
- P271 - Use only outdoors or in a well-ventilated area.
- P272 - Contaminated work clothing should not be allowed out of the workplace
- P273 - Avoid release to the environment
- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P285 - In case of inadequate ventilation wear respiratory protection

#### Response Precautionary Statements:

- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
- P302+352 - IF ON SKIN: Wash with soap and water
- P303+361+353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
- P306+360 - IF ON CLOTHING: Rinse immediately contaminated clothing and skin with plenty of water before removing clothes
- P312 - Call a POISON CENTRE or doctor/physician if you feel unwell.
- P314 - Get medical advice/attention if you feel unwell.
- P332+313 - If skin irritation occurs: Get medical advice/attention
- P337+313 - If eye irritation persists get medical advice/attention
- P362 - Take off contaminated clothing and wash before reuse.
- P370+P378 - In case of fire: Use Foam, Dry Chemical Powder, Carbon Dioxide, Fine Water Spray or Fog (for large fires only) for extinction
- P391 - Collect spillage

#### Storage Precautionary Statements:

- P403+233+235: Store in a well ventilated place. Keep container tightly closed. Keep cool
- P405 - Store locked up

#### Disposal precautionary statements:

- P501: Dispose of contents/container in accordance with local, regional, national and international regulations.

**Poison Schedule:** S6

## SAFETY DATA SHEET

Name: T190 Gun & Brush Wash

Page: 3 of 11

Date of Issue: 01/10/2016

### 3. COMPOSITION/INFORMATION OF INGREDIENTS

Component Name:	CAS Number:	Proportion % Weight:
Solvent naphtha petroleum, light aromatic	64742-95-6	35.0-45.0
Toluene	108-88-3	15.0-25.0
Ethyl alcohol	64-17-5	10.0-20.0
Methyl ethyl ketone	78-93-3	10.0-20.0
N-butyl acetate	123-86-4	05.0-10.0

### 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

#### Inhalation:

- Remove victim from exposure-avoid becoming a casualty. Remove all contaminated clothing and footwear.
- Allow patient to assume most comfortable position and keep warm.
- If inhalation of mists, fumes or vapour causes irritation to the nose, throat or lungs, causing coughing, wheezing or impaired motor skills, remove patient to fresh air.
- Apply artificial respiration if not breathing.
- If symptoms persist, obtain medical advice.

#### Skin:

- Remove all contaminated clothing and footwear.
- Wash contaminated area thoroughly with soap and water as soon as reasonably practicable.
- For gross contamination immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble).
- For skin burns cover with a clean dry dressing, if blistering occurs do not break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

#### Eyes:

- Immediately flush eyes with large amounts of water for at least 15 minutes.
- Method of irrigation; keep eyelids apart and away from eyes, routinely lift upper and lower eyelid away from eye while flushing with water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes.
- Removal of contact lenses should only be performed by skilled personnel.
- Transport to the nearest medical facility for additional treatment.

#### Swallowed:

- Do not induce vomiting, place person's face downwards, head lower than hips to prevent vomit entering lungs.
- Rinse mouth with water. Give water to drink.
- Avoid giving patient milk or oils.
- Observe patient carefully; withhold water if patient display signs of drowsiness or reduced awareness and possible unconsciousness.
- Seek medical advice.

#### First Aid Facilities:

- Ensure that eye wash bath and safety showers are readily accessible.

#### Advice to Doctor:

- Treat the patient symptomatically.

#### Other Information:

- For advice in an emergency, contact a Poisons Information Centre (Australia 13 11 26) or a doctor.

## SAFETY DATA SHEET

Name: T190 Gun & Brush Wash

Page 4 of 11

Date of Issue: 01/10/2016

### 5. FIRE FIGHTING MEASURES

**Hazchem Code: 3YE**

#### **Fire & Explosion Hazard:**

- Liquid and vapours are highly flammable.
- Explosion hazard when exposed to heat or flame.
- Highly flammable liquid and vapour. Vapour/air mix may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.
- Will float and can be reignited on surface water.
- Containers may rupture violently when exposed to extreme heat.
- On combustion the following products may be produced; Carbon Dioxide, Carbon Monoxide, Soot and Toxic smoke.

#### **Fire Fighting:**

- Evacuate immediate area of non-emergency personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Wear full protective equipment including self-contained breathing apparatus.
- Fight fire from a safe distance, with adequate cover and safe fire escape exit.
- Use foam, dry chemical or carbon dioxide extinguishers. Fine water spray may be used to cool containers to prevent vapour pressure build up.
- Prevent water runoff from entering storm water drains or waterways.

### 6. ACCIDENTAL RELEASE MEASURES

#### **Minor Spills:**

- Clean up all spills immediately.
- Eliminate all sources of ignition
- Wear full protective clothing (refer section 8)
- Avoid breathing vapours and contact with skin and eyes.
- Contain and absorb using earth, sand, vermiculite or other absorbent material. DO NOT USE sawdust, this is flammable.
- Collect residues in a flammable waste container and dispose of according to local waste management regulations.
- Do not allow product to enter storm water drains or waterways.
- Immediately remove all contaminated clothing after containment.

#### **Major Spills:**

- Evacuate personnel from immediate area and move upwind.
- Alert Fire Brigade of location and nature of hazard
- Eliminate all sources of ignition
- Wear full protective clothing (refer section 8)
- If safe to do so eliminate source of spillage.
- Avoid breathing vapours and contact with skin and eyes.
- Prevent, by any means available, spillage from entering storm water drains or water ways.
- If possible contain and absorb using earth, sand, vermiculite or other absorbent material. DO NOT USE sawdust, this is flammable.
- Use only anti-spark/ anti-static equipment to contain and remove spillage.
- Recoverable product should be collected into labeled flammable containers for recycling.
- Collect residues in a flammable waste container and dispose of according to local waste management regulations.
- Immediately remove all contaminated clothing after containment.

## SAFETY DATA SHEET

Name: T190 Gun & Brush Wash

Page 5 of 11

Date of Issue: 01/10/2016

<b>7. HANDLING AND STORAGE</b>
--------------------------------

**Safe Storage:**

- Store product in accordance with Local State, or Territory Dangerous Goods Regulations.
- Keep containers closed when not in use.
- Store in a cool, dry, well-ventilated area out of direct sunlight, away from sources of heat or ignition.
- Do store in areas where vapours may be concentrated i.e. pits, basements, or unventilated storage area.
- For containers, or container linings use mild steel, stainless steel. Unsuitable Materials: Natural, butyl, neoprene or nitrile rubbers.
- Do not store or load on the same vehicle as Class 1, Class 2.1, Class 2.3, Class 4.2, Class 5.1, Class 5.2 or Class 7 materials.

**Precautions for safe handling:**

- Wear appropriate personal protective equipment and clothing to prevent exposure.
- Do not smoke in storage/work area.
- Avoid skin and eye contact and breathing in vapour.
- All material handling equipment in work area must be flameproof.
- All nearby equipment should be earthed
- All potential sources of ignition must be eliminated from storage/work area.

<b>8. EXPOSURE CONTROLS AND PERSONAL PROTECTION</b>
---

**Occupational Exposure Limits:** No value assigned for this specific product by Safe Work Australia: Hazardous Substances Information System (HSIS).

**Concentration Cut-off Levels:**

A concentration cut-off level for a substance is the level (expressed as a percentage on a weight/weight basis for solids and liquids and a volume/volume basis for gases) at and above which that substance is classified as a hazardous substance. A mixture is classified as a hazardous substance if it contains at least one ingredient at a concentration equal to, or above, the lowest concentration cut-off level given for that ingredient.

Concentration cut-off levels refer to health hazards only, and are not associated with the physicochemical or environmental hazards of a substance. The health effects of certain types of hazardous substances are regarded as additive. Due to additive effects, a mixture may be classified as hazardous even if all of the individual substances in the mixture are present at levels below their respective cut offs.

- Reportable exposure limits for individual components that exceed **Concentration Cut Off levels:**

Chemical Name	CAS. No	TWA (8hr)		STEL		Source	Notices	%weight
		ppm	mg/m3	ppm	mg/m3			
• Solvent naphtha, petroleum, light aromatic	64742- 95- 6	Not assigned						<45.00
• Toluene	108-88-3	50	191	150	574		Sk	<25.00
Ethyl alcohol	64-17-5	50	152				Sk	<20.00
Methyl ethyl ketone	78-93-3	150	445	300	890		Eu;A	<20.00
N-butyl acetate	123-86-4	150	713	200	950	N/Eu;A		<10.00

**Source:**

A Listed in the National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC: 1003(1995).

Eu Listed in the European Union's Annex I of the EEC Council Directive 67/548/EEC (as updated by EEC Council Directive 2001/59/EC).

NIOSH National Institute for Occupational Safety and Health.

NZWES New Zealand Workplace Exposure Standards and Biological Exposure Indices 7th edition

Sk Absorption through the skin may be a significant source of exposure.

(a) The value for inhalable dust containing no asbestos and less than 1.0% free silica.

ACGIH American Conference of Governmental Industrial Hygienists

## SAFETY DATA SHEET

Name: T190 Gun & Brush Wash

Page 6 of 11

Date of Issue: 01/10/2016

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable.

Exposed individuals may be desensitised to product and are not reasonably expected to be warned, by smell, that exposure standard is being exceeded.

If the TWA concentration of ANY of the components is exceeded the individual is deemed to be over exposed.

If the directions for use on the Product Label/Safety Data Sheet are followed, exposure using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:**

**Biological Exposure Index (BEI):**

Material	Determinant	Sampling Time	BEI	Reference
Toluene	Methylhippuric acids in urine	End of shift	1.6 g/g creatine	ACGIH (2003)
	o-cresol in urine	End of shift	0.5mg/l	ACGIH (2003)
	Toluene in Blood	Prior to last shift of work week	0.02mg/l	ACGIH BEL(01 2010)
	o-Cresol, with hydrolysis	End of shift	0.3mg/g	ACGIH BEL(01 2010)
Methyl ethyl ketone	Creatinine in urine	End of shift	0.03mg/l	ACGIH BEL(01 2010)
	Toluene in urine	End of shift		
Methyl ethyl ketone	MEK in Urine	End of shift	2.0mg/l	ACGIH BEL(2008)
		End of shift		

**Engineering Controls:** Use process enclosures, local exhaust ventilation or other engineering controls to maintain worker exposure to airborne contaminants below any recommended or statutory limits. Keep containers closed when not in use. Ensure exhaust air does not contaminate other work spaces.

Vapour heavier than air - Prevent vapours concentrating in work pits, tanks or sumps. DO NOT enter confined spaces where vapour may have collected.

Ensure electrical equipment is in accordance with applicable regulations.

Equipment used to transfer product should be adequately earthed.

Ventilation equipment should be explosion/flame resistant.

Do not use near ignition sources.

**Personal Protection:** Avoid contact with skin and eyes. Wear suitable clothing such as impervious overalls, PVC, or Neoprene gloves, and safety goggles. Where workplace ventilation is assessed as inadequate and vapours/mists are generated, the use of an approved Half or Full Face Respirator with Type A-P Filter complying with Australian Standards AS1715/1716 is recommended. Select a filter suitable for organic gases and vapours rated for; [boiling point > 65°C]. If working in confined spaces with inadequate ventilation, wear an air-fed full face mask.



**Confined Space Application:**



**Flammability:** Highly flammable. Avoid heat and sources of ignition. Container should be earthed when pouring.

### 9. PHYSICAL AND CHEMICAL PROPERTIES:

**Appearance:** Colourless Liquid.

**Odour:** Aromatic/Ketone

**Decomposition Temperature:** Not available

**Boiling Point (°C):** 78

**Solubility in Water:** Below 0.1% Mass

**Solubility in Organic Solvents:** Soluble in hydrocarbons and acetone.

**Density:** 0.810 kg/l

**Flashpoint (°C):** -4.0 (Abel)

**Flammability:** Highly flammable

**Auto-ignition temperature (°C):** 350

**Explosion/Flammability Limits (% by Volume):** Not available

## SAFETY DATA SHEET

Name: T190 Gun & Brush Wash  
Page 7 of 11  
Date of Issue: 01/10/2016

<b>10. STABILITY AND REACTIVITY:</b>
--------------------------------------

**Chemical stability:** Stable under normal conditions of storage and use.

**Do not store:** In areas of extreme heat generated by naked flame or heating element.  
In the presence of incompatible materials. Refer Section 7.

**Reactivity and Stability:** Reacts with incompatible materials.

**Incompatible materials:** Strong oxidizing agents.

**Hazardous Decomposition Products:** Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

**Possibility of hazardous reactions:** Not available

<b>11. TOXICOLOGICAL INFORMATION:</b>
---------------------------------------

**Acute Toxicity: Refer Table 1 Section 16:**

Chemical Name	Cas.No	Result	Species	Dose	Exposure
Solvent naphtha (petroleum), light aromatic	64742-95-6	LD50 Oral	Rat	>2000mg/kg	4 hours
		LD50 Dermal	Rabbit	>2000mg/kg	
		LC50 Inhalation	Rat	>20mg/l	
Toluene	108-88-3	LD50 Oral	Rat	>2000mg/kg	4 hours
		LD50 Dermal	Rat	>2000mg/kg	
		LC50 Inhalation	Rat	>20mg/L	
Ethyl alcohol	64-17-5	LD50 Oral	Rat	>2000mg/kg	
Methyl ethyl ketone	78-93-3	LD50 Oral	Rat	2737mg/kg	4 hours
		LD50 Dermal	Rabbit	6480mg/l	
		LC50 Inhalation	Mouse	32000mg/l	
		LC50 Inhalation	Mammal	38000mg/l	
N-butyl acetate	123-86-4	LD50 Oral	Rat	14130mg/l	
		LD50 Dermal	Rabbit	>16mg/kg	

**Acute - Oral:** May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, oesophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.

**Acute - Eye:** Irritating to the eyes. The symptoms may include redness, itching and tearing.

**Acute - Skin:** Irritating to the skin. Has a degreasing action on the skin. Repeated or prolonged skin contact may lead to contact dermatitis and toxic effects.

**Acute - Inhaled:** Vapour may be an irritant to mucous membranes and respiratory tract.

Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and, if exposure is prolonged, unconsciousness. Harmful if inhaled.

**Respiratory sensitisation:** Not expected to be a respiratory sensitiser.

**Skin Sensitisation:** Not expected to be a skin sensitiser.

**Mutagenicity:** Not expected to be mutagenic.

**Carcinogenicity:** Not considered to be a carcinogenic hazard.

**Reproductive Toxicity:** May damage fertility or the unborn child. Classified as a known or presumed human reproductive or developmental toxicant.

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**STOT-single exposure:** May cause drowsiness or dizziness.

**STOT-repeated exposure:** May cause damage to organs through prolonged or repeated exposure.



## SAFETY DATA SHEET

Name: T190 Gun & Brush Wash  
Page: 8 of 11  
Date of Issue: 01/10/2016

### 11. TOXICOLOGICAL INFORMATION:

**Other Information:**

**Repeated Dose Toxicity:**

Central nervous system: repeated exposure affects the nervous system. Effects were seen at high doses only.  
Kidney: caused kidney effects in male rats which are not considered relevant to humans  
Auditory system: prolonged and repeated exposures to high concentrations have resulted in hearing loss in rats.  
Solvent abuse and noise interaction in the work environment may cause hearing loss. (Toluene)  
Visual system: may cause decreased colour perception. These subtle changes have not been found to lead to functional colour vision deficits. (Toluene)  
Respiratory system: repeated exposure affects the respiratory system. Effects were seen at high doses only. (Toluene)

### 12. ECOLOGICAL INFORMATION:

No value has been assigned for T190 Gun & Brush Wash. The available ecological data is given below.

**Aquatic Ecotoxicity**

Chemical Name	Cas.No	Species	Result	Method	Exposure
Solvent naphtha (petroleum), light aromatic	64742-95-6	Fish Aquatic Invertebrates Algae Microorganisms	1<LC/EC/IC50<=10mg/L 1<LC/EC/IC50<=10mg/L 1<LC/EC/IC50<=10mg/L LC/EC/IC50>100mg/L expected low toxicity		
Toluene	108-88-3	Fish Aquatic Crustacea Algae	1<LC/EC/IC50<=10mg/L 10<LC/EC/IC50<=100mg/L LL/EL/IL50>100mg/L		
Ethyl alcohol	64-17-5	Fish Aquatic Crustacea Algae Microorganisms	LL/EL/IL50 > 100 mg/l LL/EL/IL50 > 100 mg/l LL/EL/IL50 > 100 mg/l LL/EL/IL50 > 100 mg/l Practically non-toxic:		
Methyl ethyl ketone	78-93-3	Fish (fathead minnow) Aquatic Crustacea (Water flea)	LC50 - 3130-3320mg/l LC50 - >520mg/l EC50 - 7060mg/l		96 hours 48 hours 24 hours
N-butyl acetate	123-86-4	Fish (Fathead minnow) Aquatic Crustacea (Water flea)	LC50 - 18mg/l LC50 - 44mg/l		96 hours 48 hours

**Chronic Aquatic Ecotoxicity**

Toluene	108-88-3	Fish Aquatic Crustacea Algae	NOEC/NOEL > 1.0 - <=10 mg/l (based on test data) NOEC/NOEL > 1.0 - <=10 mg/l (based on test data) NOEC/NOEL > 1.0 - <=10 mg/l (based on test data)		
Ethyl alcohol	64-17-5	Fish Aquatic Crustacea	NOEC/NOEL expected to be > 100 mg/l (based on modeled data) NOEC/NOEL > 1.0 - <=10 mg/l		
N-butyl acetate	123-86-4	Algae	EC50 - 648mg/l		72 hours

**Persistence and Biodegradability:** Readily biodegradable. Oxidises rapidly by photo-chemical reactions in air.

**Bioaccumulative Potential:** Does not bioaccumulate significantly.

**Mobility in Soil:** Floats on water. If product enters soil, it will be highly mobile and may contaminate groundwater.

**Other Adverse Effects:** In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life.

**Environmental Protection:** Prevent this material entering waterways, drains and sewers.



## SAFETY DATA SHEET

Name: T190 Gun & Brush Wash

Page: 9 of 11

Date of Issue: 01/10/2016

### 13. DISPOSAL CONSIDERATION:

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used. See "Section 8. Exposure Controls and Personal Protection" of the SDS.

**Material Disposal:** Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

**Container Disposal:** Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Refer to Section 7 before handling the product or containers. Residues may cause an explosion hazard if heated above flash point. Do not puncture, cut or weld uncleaned drums. Send to drum or metal recyclers.

**Local Legislation:** Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

### 14. TRANSPORT INFORMATION:

Classified as Dangerous Goods by criteria of the Australian Dangerous Goods Code (ADG Code) for transport by road or rail.



**Product Name:** T190 Gun & Brush Wash

**Other Names:** Paint Thinner

**Manufacturer's Product Code:** T190

**UN Number:** 1263

**Packaging Group:** II

**Dangerous Goods Class & Subsidiary Risk:** 3

**Hazchem Code:** •3YE

**Limited Quantity:** 5 litre

**Declaration for land shipment:** Flammable Liquid / Paint Related Material

**Proper Shipping Name:** PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

**Air Transport IATA:**

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA), Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

**Product Name:** T190 Gun & Brush Wash

**ICAO/IATA Class:** 3

**Special Provisions:** 3A

**UN No:** 1263

**Packaging Group:** II

**Packaging Instructions (passenger & cargo):** 353

**Packaging Instructions (cargo only):** 364

**Shipping name:** Flammable Liquid / Paint Related Material

**Proper Shipping Name:** PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

**Marine Transport:**

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

**Product Name:** T190 Gun & Brush Wash

**UN No:** 1263

**Class-primary:** 3 Flammable Liquid

**Packing Group:** II

**Shipping Name:** Flammable Liquid / Paint Related Material

**EMS:** F-E, SE

**Special Provisions:** 363

**Proper Shipping Name:** PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

## SAFETY DATA SHEET

Name: T190 Gun & Brush Wash

Page: 10 of 11

Date of Issue: 01/10/2016

### 14. TRANSPORT INFORMATION:

Do not load on the same vehicle as:

- Class 1: Explosives
- Class 2.1: Flammable Gases
- Class 2.3: Toxic Gasses
- Class 4.2: Spontaneously Combustible Substances
- Class 5.1: Oxidising Agents
- Class 5.2: Organic Peroxides
- Class 7: Radioactive Substances

### 15. REGULATORY INFORMATION

**Poison Schedule:** S6

**Individual components of T190 Gun & Brush Wash on regulatory listings:**

Solvent naphtha (petroleum), heavy aromatic: **CAS No: 64742-94-5:** ACIS, DSL, INV(CN), TSCA, EINECS, KECI, PICCS

Toluene: **CAS No: 108-88-3:** AICS, DSL, ENCS, TSCA, EINECS, KECI, PICCS, IVN (CN), IRAC.

Ethyl alcohol: **CAS No: 64-17-5:** AICS, NZIoC, DSL, ENCS, IECSC, ISHL, KECI, PICCS.

Methyl ethyl ketone: **CAS No: 78-93-3:** AICS, DSL, ENCS, TSCA, EINECS, KECI, PICCS, IVN (CN), IRAC, NZIoC.

N-butyl acetate: **CAS No: 124-86-4:** ACIS, NICNAS, DSL, TSCA, MITI, KECL.

#### IRAC GROUP CLASSIFICATION:

Group 1 Carcinogenic to humans:

Group 2A Probably carcinogenic to humans:

Group 2B Possibly carcinogenic to humans:

Group 3 Not classifiable as to its carcinogenicity to humans: CAS No: 108-88-3

Group 4 Probably not carcinogenic to humans:

### 16. OTHER INFORMATION:

**CAS No:** CAS Registry Number is a unique numeric identifier that designates only one substance. It has no chemical significance.

**TWA:** Exposure standard-time weighted average; the average airborne concentration of a particle substance when calculated over a normal eight hour working day, for a five day week.

**STEL:** Short-term exposure limit (STEL) is the acceptable exposure limit to a toxic or an irritant substance over a short period of time (time-weighted average), usually 15 minutes. STEL is the maximum concentration of a chemical to which workers may be exposed continuously for a short period of time without any danger to health, safety or work efficiency.

**ppm:** Parts of vapour or gas per million parts of contaminated air by volume.

**mg/m<sup>3</sup>:** Milligrams of substance per cubic metre of air at 25°C and one atmosphere pressure. When entry is in this column only the value is exact; when listed with a ppm value, it is approximate.

**LD50:** Lethal Dosage represents the individual dose required to kill 50 percent of a population of test animals.

**LC50:** Lethal Concentrations of the chemical in air that kills 50% of the test animals during the observation period of time (traditional 4 hours). It can also mean the concentration of a chemical in water.

**EC50:** The Median Effective Concentration is the statistically derived concentration of a substance in an environmental medium expected to produce a certain effect in 50% of test organisms in a given population under a defined set of conditions.

## SAFETY DATA SHEET

Name: T190 Gun & Brush Wash  
Page: 11 of 11  
Date of Issue: 01/10/2016

**16. OTHER INFORMATION:**

**IC50:** Half Maximal Inhibitory Concentration is a measure of the effectiveness of a substance in inhibiting a specific biological or biochemical function. This quantitative measure indicates how much of a particular drug or other substance is needed to inhibit a given biological process (or component of a process, i.e. an enzyme, cell, cell receptor or microorganism) by half.

**LDL0:** Lethal Dose Low, lowest dose of a substance reported to have caused death in humans or animals.

**NOEC/NOEL:** No Observable Effect Concentration/Level

**Toxicity classification: Table 1**

Toxicity Classes: Hodge and Sterner Scale					
		Route of Administration			
Toxicity Rating	Common Term	Oral LD50	Inhalation LC50	Dermal LD <sub>50</sub>	Probable Lethal Dose for Man
		(single dose to rats) mg/kg	(exposure of rats for 4 hours) ppm	(single application to skin of rabbits) mg/kg	
1	Extremely Toxic	1 or less	10 or less	5 or less	1 grain (a taste, a drop)
2	Highly Toxic	1 to 50	10 to 100	5 to 43	4 ml (1 tsp)
3	Moderately Toxic	50 to 500	100 to 1000	44 to 340	30 ml (1 fl. oz.)
4	Slightly Toxic	500 to 5000	1000 to 10000	350 to 2810	600 ml (1 pint)
5	Practically Non Toxic	5000 to 15000	10000 to 100000	2820 to 22590	1 litre (or 1 quart)
6	Relatively Harmless	15000 or more	100000 or more	22600 or more	1 litre (or 1 quart)

**Toxicity classification: Table 2**

LC/EC/IC50	< 1 mg/l	very high toxicity
LC/EC/IC50	1-10 mg/l	high toxicity
LC/EC/IC50	10-100 mg/l	moderate toxicity
LC/EC/IC50	>100 mg/l	low toxicity

**SDS Effective Date:** 01/10/2016

**SDS Distribution:** The information in this document should be made available to all who may handle the product.

CONTACT POINT		
<b>Technical Manager</b>	- Working hours	(02) 9688-1999
	- After hours	(02) 9636-5505

Although this information is presented in good faith and compiled from various sources believed to be accurate, Lacnam Paints make no representations or warranty as to the completeness or accuracy thereof. As the product's performance and suitability depends on various factors, the purchasers of our products should determine for themselves whether the product is suitable for their particular use.

**Hazardous according to criteria of Australian Safety Compensation Council**