



LACNAM PAINTS AUSTRALIA

ABN 48 125 092 482

78-80 MANDOOK, ROAD, GIRRAWEE, SYDNEY

NSW 2145 AUSTRALIA

TELEPHONE: (02) 9688 1999 FACSIMILE: (02) 9896 1606

EMAIL: sales@lacnam.com.au WEBSITE: www.lacnam.com.au

TECHNICAL INFORMATION SHEET

299 PAINT STRIPPER

May 2009

TDS 299 page 1 of 2

Description and uses

299 Paint Stripper is a solvent based, heavy bodied paint remover recommended for removal of most types of paints and lacquers.

299 Paint Stripper has the following features:

- Fast acting and non-caustic
- Non-staining
- Harmless to timber and metal surfaces

Typical areas of application are:

- Light industrial environments
- Metal fabrications and industries
- Restoration work

Application

Apply a heavy film of 299 Paint Stripper to the surface to be treated by brush. Allow existing paint coatings to wrinkle, and then scrape off with a paint scraper or hose down using a high pressure water jet.

Repeat above instructions until all paint is removed. Surfaces should be washed down with remover prior to painting.

299 PAINT STRIPPER

May 2009

TDS 299 page 2 of 2

Safety Instructions:

Caution: 299 Paint Stripper contains Dichloromethane; container may build up pressure on storage.

Storage: Store in a cool, dry bunded area out of direct sunlight as required for Flammable liquids DG Class 6, PG III, Hazchem 2Z.

Flammability: Non flammable.

Handling: Adopt adequate Occupational Work Practices to avoid personal contamination with product. Always wash hands before smoking, eating, drinking or using toilet. Food and Drink should be stored and consumed in separate area.

Personal Protection: Avoid contact with skin or eyes; wear suitable clothing such as impervious overalls, PVC or neoprene gloves, safety goggles and face mask.

Using: Avoid inhalation of spray mist and vapours – use with adequate ventilation and suitable Personal Protection Equipment (PPE).

Engineering controls: Ensure ventilation is adequate. When spraying, ensure product is applied in a fully functional spray-booth. Keep containers closed when not in use. Do not use near ignition sources.

REFER MSDS BEFORE USE

(Phone 02 9688 1999 or refer to www.lacnam.com.au for copy MSDS)

Although this information is presented in good faith and compiled from sources believed to be accurate, Lacnam Paints make no representations or warranty as to the completeness or accuracy thereof. As the product's performance and suitability depends on various factors, the purchasers of our products should determine for themselves whether the product is suitable for their particular use.