



## MATERIAL SAFETY DATA SHEET

### 1. IDENTIFICATION OF MATERIAL & COMPANY DETAILS

**Product Name: 405 AEROSOL SPRAY 390 ENAMEL**

Company Name: Lacnam Paints Australia  
Address: 78-80 Mandoon Road, Girraween, NSW 2145  
Telephone Number: (02) 9688-1999  
Emergency Number: (02) 9636-5505 (after hours)

### 2. HAZARDS IDENTIFICATION

HAZARDOUS SUBSTANCE-DANGEROUS GOODS:  
Classified as hazardous according to criteria of ASCC.  
Classified as dangerous according to Dangerous Good Code.

Xn Harmful  
Xi Irritant

**Risk Phrases:**

R11 Highly Flammable  
R20/21/22 Harmful by Inhalation, in contact with skin and if swallowed.  
R36/37/38 Irritating to eyes, respiratory system and skin.  
R41 Risk of serious eye damage.  
R43 May cause sensitization by skin contact.  
R51 Toxic to aquatic organisms  
R53 May cause long-term adverse effects in the aquatic environment.  
R65 Harmful: May cause lung damage if swallowed.  
R66 Repeated exposure may cause skin dryness and cracking.  
R67 Vapours may cause drowsiness and dizziness.

**Safety Phrases:**

S2 Keep out of reach of children.  
S7 Keep container tightly closed.  
S9 Keep container in well ventilated place.  
S13 Keep away from food, drink, and animal feeding stuffs.  
S15 Keep away from heat.  
S16 Keep away from sources of ignition-No smoking.  
S23 Do not breathe gas/fumes/vapour/spray.  
S24 Avoid contact with skin.  
S25 Avoid contact with eyes.  
S26 In case of contact with eyes, immediately rinse with plenty of water and seek medical advice.

# MATERIAL SAFETY DATA SHEET

405 Aerosol Spray 390 Enamel

Page 2 of 6

Date of issue 06 May 2008

## 2. HAZARDS IDENTIFICATION

S27	Take off immediately all contaminated clothing.
S29	Do not empty into drains.
S33	Take precautionary measures against static discharges.
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
S38	In case of insufficient ventilation, wear suitable respiratory equipment.
S43	In case of fire use: Foam, Dry chemical powder, Carbon dioxide, Water spray or fog (for large fires only) as extinguishing media.
S51	Use only in well ventilated areas.
S61	Avoid release to the environment.
S62	If swallowed, do not induce vomiting: seek medical advice immediately and show this label or can.

## 3. COMPOSITION/INFORMATION OF INGREDIENTS

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Proportion</u>
Alkyd Resins	Proprietary	50-70%
Pigments	Proprietary	20-40%
Liquid Hydrocarbons	9005-90-7	5-15%
Liquid Hydrocarbons	64742-95-6	5-10%
Alcohols	71-36-3	1-5%
Additives	Proprietary	1-5%
Butane	106-97-8	5-10%
Propane	74-98-6	5-10%

## 4. FIRST AID MEASURES

<b>Inhalation:</b>	If inhalation of mists, fumes or vapour causes irritation to the nose or throat, or coughing, remove to fresh air. If symptoms persist, obtain medical advice.
<b>Skin:</b>	Remove all contaminated clothing and footwear. Wash contaminated area thoroughly with soap and water as soon as reasonably practicable.
<b>Eyes:</b>	Immediately flush eyes with large amounts of water for at least 15 minutes while holding eyelids open. Transport to the nearest medical facility for additional treatment.
<b>Swallowed:</b>	Rinse mouth with water. Give water to drink. Do not induce vomiting. If vomiting occurs, place person's face

# MATERIAL SAFETY DATA SHEET

405 Aerosol Spray 390 Enamel

Page 3 of 6

Date of issue 06 May 2008

## 4. FIRST AID MEASURES

downwards, head lower than hips to prevent vomit entering lungs. Seek medical advice.

**First Aid Facilities:** Ensure that an eye wash bath and safety shower, are readily accessible.

**Advice to Doctor:** Treat the patient symptomatically.

## 5. FIRE FIGHTING MEASURES:

Evacuate immediate area of non-emergency personnel.

Risk of explosion when containers exposed to extreme heat.

On combustion the following products may be produced. Carbon Dioxide, Carbon Monoxide, Soot, Smoke.

Use foam, dry chemical or carbon dioxide extinguishers. Water spray may be used to cool containers to prevent vapour pressure build up. Wear full protective equipment including self-contained breathing apparatus.

## 6. ACCIDENTAL RELEASE MEASURES:

Eliminate all sources of ignition. Wear full protective equipment. Contain and absorb using earth, sand or other inert material, do not use sawdust, this is flammable. Transfer into containers for disposal according to local regulations. Do not allow product to enter drains or water courses. Immediately remove all contaminated clothing after containment.

## 7. HANDLING AND STORAGE:

Store product in accordance with State, or Territory Dangerous Goods regulations. Store in a cool place away from direct sunlight. Do not load on the same vehicle as Class 1, Class 3 (where both are bulk), Class 4.2, Class 5.1, Class 5.2 or Class 7.

# MATERIAL SAFETY DATA SHEET

405 Aerosol Spray 390 Enamel

Page 4 of 6

Date of issue 06 May 2008

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

No evaluated data available for 405 Aerosol Spray 390 Enamel.

### Hazardous Components Data:

Chemical Type:	CAS. No	TWA (Refer Section 16)	
		ppm	mg/m <sup>3</sup>
Liquid Hydrocarbon	64742-95-6	55	270
Liquid Hydrocarbon	9005-90-7	90	480
Alkyd Resin	Proprietary		480
Alkyd Resin	Proprietary	100	
Butane	106-97-8	800	1900
Propane	74-98-6	1000	1804

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

Based on available information on hazardous components of this product, the recommended exposure limit, (TWA) is 100 ppm.

**Engineering Controls:** Ensure ventilation is adequate. When spraying, ensure product is applied in a fully functional spray-booth. Keep containers closed when not in use. Do not use near ignition sources.

**Personal Protection:** Avoid contact with skin and eyes. Wear suitable clothing such as impervious overalls, PVC or Neoprene gloves, and safety goggles. Wear an approved half-face respirator, minimum requirement class P3 particle filter and suitable Organic Gas Filter rated for; [boiling point < 65°C] suitable for organic vapour and particles, meeting AS1715/1716. In confined spaces with inadequate ventilation, wear an air-fed face mask.

**Flammability:** Highly flammable. Avoid heat and sources of ignition. Do not puncture container.

## 9. PHYSICAL AND CHEMICAL PROPERTIES:

**Appearance:** Coloured viscous liquid.

**Boiling/Melting Point (°C):** -42 (Propane) / Not available

**Vapour Pressure:** Not available

**Specific Gravity:** 1.1 - 1.4 depending on colour

**Flashpoint (°C):** -104 (Propane)

**Auto-ignition temperature (°C):** 430 (Butane)

**Flammability Limits (% by Volume):** Not available

**Solubility in Water:** Nil

# MATERIAL SAFETY DATA SHEET

405 Aerosol Spray 390 Enamel

Page 5 of 6

Date of issue 06 May 2008

## 10. STABILITY AND REACTIVITY:

**Do not store:** In areas of extreme heat generated by naked flame or heating element.  
In the presence of incompatible materials.  
In direct sunlight.

**At Ambient Temperature:** Product is considered stable.  
Hazardous polymerisation will not occur.

## 11. TOXICOLOGICAL INFORMATION:

**Acute - Swallowed:** May cause irritation to mouth, throat and digestive tract. Large dose may cause drowsiness and may lead to unconsciousness.

**Acute - Eye:** Irritating to the eyes.

**Acute - Skin:** Irritating to the skin. Has a degreasing action on the skin. Repeated or prolonged skin contact may lead to contact dermatitis and toxic effects.

**Acute - Inhaled:** Vapour may be an irritant to mucous membranes and respiratory tract.

## 11. TOXICOLOGICAL INFORMATION:

Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and, if exposure is prolonged, unconsciousness.  
Harmful if inhaled.

**Chronic:** Repeated or prolonged exposure to this chemical could result in central nervous system disorders.

## 12: ECOLOGICAL INFORMATION:

Prevent release into the environment.  
Do not discharge into sewer or waterways.  
May cause adverse effects to marine organisms.  
May cause adverse effects to marine environment.

## 13: DISPOSAL CONSIDERATIONS:

Refer to State Land Waste Management Authority. Advice flammable nature of product.  
Recycle containers if possible, or dispose of in authorised landfill.  
Do not puncture or burn can even when empty.

# MATERIAL SAFETY DATA SHEET

405 Aerosol Spray 390 Enamel

Page 6 of 6

Date of issue 06 May 2008

## 14: TRANSPORT INFORMATION:



Classified as Dangerous Goods by criteria of the Australian Dangerous Goods Code (ADG Code) for transport by road or rail.

**Product Name:** 405 Aerosol 390 Enamel  
**Other Names:** Aerosol Paint  
**Manufacturer's Product Code:** 405  
**UN Number:** 1950  
**Packaging Group:** II  
**Dangerous Goods Class & Subsidiary Risk:** 2  
**Hazchem Code:** 2[Y]E  
**Use:** Spraying Enamel

Class 2.1 should not be loaded on the same vehicle as Classes 1, 3 (where both are in bulk), 4, 5, and 7.

## 15: REGULATORY INFORMATION:

**Poisons Schedule:** Not Allocated.

## 16: OTHER INFORMATION:

**TWA:** Exposure standard-time weighted average; the average airborne concentration of a particle substance when calculated over a normal eight hour working day, for a five day week.

**ppm:** Parts of vapour or gas per million parts of contaminated air by volume.

**mg/m<sup>3</sup>:** Milligrams of substance per cubic metre of air at 25°C and one atmosphere pressure. When entry is in this column only the value is exact; when listed with a ppm value, it is approximate.

**WARNING:** Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

## CONTACT POINT

Technical Manager	- Working hours	(02) 9688-1999
	- After hours	(02) 9636-5505

Although this information is presented in good faith and compiled from various sources believed to be accurate, Lacham Paints make no representations or warranty as to the completeness or accuracy thereof. As the product's performance and suitability depends on various factors, the purchasers of our products should determine for themselves whether the product is suitable for their particular use.

**Hazardous according to criteria of Australian Safety Compensation Council**