



MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION OF MATERIAL & COMPANY DETAILS

Product Name: T109 ENAMEL THINNER [SLOW]:

Company Name: Lacnam Paints Australia
Address: 78-80 Mandoon Road, Girraween, NSW 2145
Telephone Number: (02) 9688-1999
Emergency Number: (02) 9636-5505 (after hours)

2. HAZARDS IDENTIFICATION

HAZARDOUS SUBSTANCE-DANGEROUS GOODS:
Classified as hazardous according to criteria of ASCC.
Classified as dangerous according to Dangerous Good Code.

Xn Harmful.
N Dangerous to the environment.

Risk Phrases:

R11 Highly Flammable.
R20 Harmful by Inhalation.
R37 Irritating to eyes and respiratory system.
R51 Toxic to Aquatic Organisms.
R53 May cause long term adverse effects in the aquatic environment.
R65 Harmful. May cause Lung Damage if swallowed.
R66 Repeated exposure may cause skin dryness and cracking.
R67 Vapours may cause drowsiness and dizziness.

Safety Phrases:

S2 Keep out of reach of children.
S16 Keep away from sources of ignition – NO SMOKING.
S23 Do not breathe gas, fumes, vapour or spray.
S24 Avoid contact with eyes.
S33 Take precautionary measures against static discharges
S36 Wear suitable protective clothing.
S43 In case of fire, use recommended fire extinguishers: Carbon Dioxide, Dry Chemical or Foam.
S61 Avoid release to the environment, Refer special instructions.
S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

MATERIAL SAFETY DATA SHEET

T109 Enamel Thinner [Slow]

Page 2 of 5

Date of issue 13 Feb 2009

3. COMPOSITION/INFORMATION OF INGREDIENTS

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Proportion</u>
Liquid Hydrocarbons	64742-94-5	40-60%
Liquid Hydrocarbons	108-88-3	15-30%
Liquid Hydrocarbons	95-63-6	10.0-<20.0%
Liquid Hydrocarbons	1330-20-7	5.0-<10.0%
Liquid Hydrocarbons	108-67-8	5.0-<10.0%
Liquid Hydrocarbons	98-82-8	<5.0%
Liquid Hydrocarbons	526-73-8	<5.0%
Liquid Hydrocarbons	103-65-1	<5.0%
Liquid Hydrocarbons	91-20-3	<5.0%

4. FIRST AID MEASURES

Inhalation: If inhalation of mists, fumes or vapour causes irritation to the nose or throat, or coughing, remove to fresh air. If symptoms persist, obtain medical advice.

Skin: Remove all contaminated clothing and footwear. Wash contaminated area thoroughly with soap and water as soon as reasonably practicable.

Eyes: Immediately flush eyes with large amounts of water for at least 15 minutes while holding eyelids open. Transport to the nearest medical facility for additional treatment.

Swallowed: Rinse mouth with water. Give water to drink. Do not induce vomiting. If vomiting occurs, place person's face downwards, head lower than hips to prevent vomit entering lungs. Seek medical advice.

First Aid Facilities: Ensure that an eye wash bath and safety shower, are readily accessible.

Advice to Doctor: Treat the patient symptomatically.

5. FIRE FIGHTING MEASURES:

Evacuate immediate area of non-emergency personnel.

On combustion the following products may be produced. Carbon Dioxide, Carbon Monoxide, Soot, Smoke.

Use foam, dry chemical or carbon dioxide extinguishers. Water spray may be used to cool containers to prevent vapour pressure build up. Wear full protective equipment including self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES:

Eliminate all sources of ignition. Wear full protective equipment. Contain and absorb using earth, sand or other inert material, do not use sawdust, this is flammable. Transfer into containers for disposal according to local regulations. Do not allow product to enter drains or water courses. Immediately remove all contaminated clothing after containment.

MATERIAL SAFETY DATA SHEET

T109 Enamel Thinner [Slow]

Page 3 of 5

Date of issue 13 Feb 2009

7. HANDLING AND STORAGE:

Keep containers closed when not in use. Store product in accordance with State, or Territory Dangerous Goods regulations. Do not load on the same vehicle as Class 1, Class 2.1, Class 2.3, Class 4.2, Class 5.1, Class 5.2 or Class 7.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

No evaluated data available for T109 Enamel Thinner [Slow].

Hazardous Components Data:

Chemical Type:	CAS. No	TWA (Refer Section 16)	
		ppm	mg/m ³
Liquid Hydrocarbons combined as:	64742-94-5	17	-
Liquid Hydrocarbon combined as:	9005-90-7	90	480
Liquid Hydrocarbon	108-88-3	50	191

Based on available information on hazardous components of this product, the recommended exposure limit, (TWA) is 35 ppm.

Exposed individuals may be desensitised to product and are not reasonably expected to be warned, by smell, that exposure standard is being exceeded.

If the TWA concentration of ANY of the components is exceeded the individual is deemed to be over exposed.

Engineering Controls: : Ensure ventilation is adequate, (typically 10 air changes per hour). If applicable use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. Flameproof equipment is necessary in the area where this product is used. All equipment should be earthed to prevent static build up. Keep containers closed when not in use. Do not use near ignition sources.

Personal Protection: Avoid contact with skin and eyes. Wear suitable clothing such as impervious overalls, PVC or Neoprene gloves, and safety goggles. Wear an approved half-face respirator suitable for organic vapour, meeting AS1715/1716. Select a filter suitable for organic gases and vapours rated for; [boiling point > 65°C]. In confined spaces with inadequate ventilation, wear an air-fed face mask.

Flammability: Highly flammable. Avoid heat and sources of ignition. Container should be earthed when pouring.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance: Colourless liquid.

Boiling/Melting Point (°C): 95/ Not available

Vapour Pressure: Not available

Specific Gravity: 0.87

Flashpoint (°C): 4.0

Auto-ignition temperature (°C): 300

Flammability Limits (% by Volume): 1-12

Solubility in Water: Below 0.1% Mass

MATERIAL SAFETY DATA SHEET

T109 Enamel Thinner [Slow]

Page 4 of 5

Date of issue 13 Feb 2009

10. STABILITY AND REACTIVITY:

Do not store: In areas of extreme heat generated by naked flame or heating element.
In the presence of incompatible materials.

At Ambient Temperature: Product is considered stable.
Hazardous polymerisation will not occur.

11. TOXICOLOGICAL INFORMATION:

Acute - Swallowed: May cause irritation to mouth, throat and digestive tract. Large dose may cause drowsiness and may lead to unconsciousness.

Acute - Eye: Irritating to the eyes.

Acute - Skin: Irritating to the skin. Has a degreasing action on the skin. Repeated or prolonged skin contact may lead to contact dermatitis and toxic effects.

Acute - Inhaled: Vapour may be an irritant to mucous membranes and respiratory tract. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and, if exposure is prolonged, unconsciousness. Harmful if inhaled.

Chronic: Repeated or prolonged exposure to this chemical could result in central nervous system disorders.

12. ECOLOGICAL INFORMATION:

Prevent release into the environment.

Do not discharge into sewer or waterways.

May cause adverse effects to marine organisms.

May cause adverse effects to marine environment.

If product enters soil, it will be highly mobile and may contaminate ground water.

13. DISPOSAL CONSIDERATIONS:

Refer to State Land Waste Management Authority. Advice flammable nature of product.

Material Disposal: Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated, and to assess the appropriate waste classification and disposal methods.

Container Disposal: Drain containers thoroughly. Vent in a safe position away from naked flames and sparks. Residue may cause an explosion. Do not puncture, cut or weld. Send to Approved Drum/Metal Recyclers.

This product is not suitable for landfill.


MATERIAL SAFETY DATA SHEET

T109 Enamel Thinner [Slow]

Page 5 of 5

Date of issue 13 Feb 2009

14: TRANSPORT INFORMATION:



Classified as Dangerous Goods by criteria of the Australian Dangerous Goods Code (ADG Code) for transport by road or rail.

Product Name: T109 Enamel Thinner [Slow]

Other Names: Paint Thinner

Manufacturer's Product Code: 109

UN Number: 1263

Packaging Group: II

Dangerous Goods Class & Subsidiary Risk: 3

Hazchem Code: 3[Y]E

Use: Thinner for Enamel Paints

Do not load on the same vehicle as Class 1, Class 2.1, Class 2.3, Class 4.2, Class 5.1, Class 5.2 or Class 7.

15: REGULATORY INFORMATION:

Poisons Schedule Number: 6

16: OTHER INFORMATION:

TWA: Exposure standard-time weighted average; the average airborne concentration of a particle substance when calculated over a normal eight hour working day, for a five day week.

ppm: Parts of vapour or gas per million parts of contaminated air by volume.

mg/m³: Milligrams of substance per cubic metre of air at 25°C and one atmosphere pressure. When entry is in this column only the value is exact; when listed with a ppm value, it is approximate.

CONTACT POINT

Technical Manager	- Working hours	(02) 9688-1999
	- After hours	(02) 9636-5505

Although this information is presented in good faith and compiled from various sources believed to be accurate, Lacnam Paints make no representations or warranty as to the completeness or accuracy thereof. As the product's performance and suitability depends on various factors, the purchasers of our products should determine for themselves whether the product is suitable for their particular use.

Hazardous according to criteria of Australian Safety Compensation Council