



**Sydney Head Office:**  
Phone: 02 9688 1999  
Fax: 02 9896 1606  
78 – 80 Mandoon Road  
Girraween, 2145, NSW  
[sales@lacnam.com.au](mailto:sales@lacnam.com.au)

TDS 220 page 1 of 2

# 220 RUST PREVENTATIVE

## Bituminous Rust Preventative

### Description and uses

A solvent based black bituminous rust preventative designed to prevent rust on clean metal surfaces. This product may slow down the rusting process on rusty surfaces, however it is not designed to remove existing rust which will continue it's ravages under the coating. 220 Rust Preventative is suitable for long term protection in exposed conditions and also protects against corrosive fumes.

**Note:** Unlike paints, petroleum based rust preventatives are meant to be temporary protectives, designed for easy removal when their job is done. It is not possible to give definite times of protections as storage conditions vary widely and affect performance considerably. For critical applications the product should be tested for its suitability.

Typical areas of application are:

- Farm equipment which is seasonally stored.
- Finished machine components.
- Transportation, marine and general construction equipment.

### Technical Specifications

FINISH: Black gloss film.

THINNERS: Mineral turps.

COVERAGE: Approximately 4-5 Square metres per litre.

APPLICATION: By brush, dip or spray.

DRYING AT 25°C: Dry in 2-3 hours. Remains a soft durable, thermoplastic film.

### Application Details-Surface Preparation

All surfaces to be painted should be clean and free from dust, dirt, oil, grease etc. Rusty surfaces should be free of any loose and powdery rust.



**Sydney Head Office:**  
Phone: 02 9688 1999  
Fax: 02 9896 1606  
78 – 80 Mandoon Road  
Girraween, 2145, NSW  
[sales@lacnam.com.au](mailto:sales@lacnam.com.au)

TDS 220 page 2 of 2

### **Application**

Brush or roller: Thinning not normally required.

Conventional spray: Thin approximately 20% then apply.

Airless spray: Thin approximately 5-10% and apply.

Dipping: Thin to a suitable viscosity for dipping. (Dipping twice may be necessary for specific applications)

Clean up: Mineral turps.

### **Safety Instructions**

Flammability: Highly flammable, avoid heat and sources of ignition. Container should be earthed when pouring.

Personal Protection: Avoid contact with skin or eyes, wear suitable clothing such as impervious overalls, PVC or neoprene gloves, safety goggles. Wear an approved half-face respirator suitable for organic vapor, meeting AS1715/1716.

Engineering controls: Ensure ventilation is adequate. When spraying, ensure product is applied in a fully functional spray-booth. Keep containers closed when not in use. Do not use near ignition sources.

Although this information is presented in good faith and compiled from sources believed to be accurate, Lacnam Paints make no representations or warranty as to the completeness or accuracy thereof. As the product's performance and suitability depends on various factors, the purchasers of our products should determine for themselves whether the product is suitable for their particular use.