



Sydney Head Office:
Phone: 02 9688 1999
Fax: 02 9896 1606
78 – 80 Mandoon Road
Girraween, 2145, NSW
sales@lacnam.com.au

TDS 291 page 1 of 1

291 WOOD PRIMER

Description and uses

291 Wood Primer is a high quality linseed oil based primer for timber which is to be topcoated with finishes suitable for application over a linseed oil or alkyd based primer.

291 Wood Primer was formulated for use with commercial machine designed to coat fascia boards and other pre-primed timber for the building industry.

Technical Specifications

FINISH: Flat pink or cream.

THINNERS: Mineral turps.

COVERAGE: Approximately 10-12 Square metres per litre.

DRYING AT 25°C: Touch dry 4-6 hours.

SURFACE PREPARATION: All surfaces should be sanded if necessary and dusted down before painting.

APPLICATION DETAILS: Can be brushed or rolled as is or with small levels of thinner addition. Machine coating- use as manufactures directions.

Safety Instructions

Flammability: Highly flammable, avoid heat and sources of ignition. Container should be earthed when pouring.

Personal Protection: Avoid contact with skin or eyes, wear suitable clothing such as impervious overalls, PVC or neoprene gloves, and safety goggles. Wear an approved half-face respirator suitable for organic vapor, meeting AS1715/1716.

Engineering controls: Ensure ventilation is adequate. When spraying, ensure product is applied in a fully functional spray-booth. Keep containers closed when not in use. Do not use near ignition sources.

Although this information is presented in good faith and compiled from sources believed to be accurate, Lacnam Paints make no representations or warranty as to the completeness or accuracy thereof. As the product's performance and suitability depends on various factors, the purchasers of our products should determine for themselves whether the product is suitable for their particular use.