

TECHNICAL INFORMATION SHEET

299 PROFESSIONAL GRADE PAINT STRIPPER

January 2021

TDS 299 page 1 of 2

Description and uses:

299 Professional Grade Paint Stripper is a solvent based, non-caustic, heavy bodied paint remover for stripping most types of household, automotive, marine, and industrial paints and lacquers.

299 Paint Stripper has the following features:

- Carefully balanced solvent formulation
- Contains evaporation retarders and thickeners.
- Fast acting and non-caustic
- Non-staining
- Harmless to timber and metal surfaces

Typical areas of application are:

- Light industrial environments
- Metal fabrications and industries
- Restoration work

Other applications include outdoor furniture, fences, timber and aluminium boats, machinery and as an automotive paint remover for cars and trucks.

Application:

Apply a heavy film of 299 Paint Stripper to the surface to be treated by brush.

Allow existing paint coating to soften and wrinkle, then scrape off with a paint scraper.

If all the paint is not removed with the first application, apply a second coat of paint stripper. Where multiple paint layers are present, several applications may be required.

When all paint coating is removed, wash down, and clean the surface. Using a scouring pad or steel wool, wash down with water or Methylated Spirits. Alternatively, a high-pressure water jet may be used.

Note: Caution should be exercised when using high-pressure water jet to prevent damage of surround surfaces from off-spray, splash, or spatter.

Timber surfaces may need a final detergent wash and sanding to remove raised timber grain.

Allow surface to dry before applying new coating system.

TECHNICAL INFORMATION SHEET

299 PROFESSIONAL GRADE PAINT STRIPPER

January 2021

TDS 299 page 1 of 2

Safety Instructions:

Caution: 299 Paint Stripper contains Dichloromethane; container may build up pressure on storage.

Storage: Store in a cool, dry bunded area out of direct sunlight as required for Flammable liquids DG Class 6, PG III, Hazchem 2Z.

Flammability: Non-flammable.

Handling: Adopt adequate Occupational Work Practices to avoid personal contamination with product. Always wash hands before smoking, eating, drinking or using toilet. Food and Drink should be stored and consumed in separate area.

Personal Protection: Avoid contact with skin or eyes; wear suitable clothing such as impervious overalls, PVC or neoprene gloves, safety goggles and face mask.

Using: Avoid inhalation of spray mist and vapours – use with adequate ventilation and suitable Personal Protection Equipment (PPE).

Engineering controls: Ensure ventilation is adequate. When spraying, ensure product is applied in a fully functional spray-booth. Keep containers closed when not in use. Do not use near ignition sources.

REFER SDS BEFORE USE

(Phone 02 9688 1999 or refer to www.lacnam.com.au for copy SDS)

Although this information is presented in good faith and compiled from sources believed to be accurate, Lacnam Paints make no representations or warranty as to the completeness or accuracy thereof. As the product's performance and suitability depends on various factors, the purchasers of our products should determine for themselves whether the product is suitable for their particular use.