

**SAFETY DATA SHEET****1. IDENTIFICATION OF MATERIAL & COMPANY DETAILS**

**Product Name:** T181 GP EPOXY THINNER

**Product description:** Solvent Mixture

**Recommended Use:** Industrial solvent for paint thinning and clean up.

**CAS Number:** Not Applicable

**Company Name:** Lacnam Paints Australia

**Address:** 76-80 Mandoon Road, Girraween, NSW 2145

**Email:** [sales@lacnam.com.au](mailto:sales@lacnam.com.au)

**Telephone Number:** (02) 9688-1999

**Emergency Number:** 0419 260 572 (after hours)

**2. HAZARDS IDENTIFICATION****HAZARDOUS SUBSTANCE-DANGEROUS GOODS:**

Classified as hazardous according to criteria of Work Safe Australia

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

**Signal Word: DANGER****GHS Classification:**

Aspiration Hazard: Category 1  
Flammable Liquids: Category 3  
Acute Toxicity Inhalation: Category 4  
Acute Toxicity Dermal: Category 4  
Acute Toxicity Oral: Category 4  
Skin Corrosion/Irritation: Category 2  
Serious Eye Damage/Eye Irritation: Category 1  
STOT Repeated Exposure: Category 2  
STOT Single Exposure: Category 3 (respiratory tract irritation)

**Hazard Statements:**

H226 - Flammable liquid and vapour  
H304 - May be fatal if swallowed and enters airways  
H312 - Harmful in contact with skin.  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H335 - May cause respiratory irritation  
H336 - May cause drowsiness and dizziness  
H373 - May cause damage to organs (hearing organs) through prolonged or repeated exposure

**Non-GHS Hazard Statement:**

AUH066 - Repeated exposure may cause skin dryness and cracking

## SAFETY DATA SHEET

Name: T181 GP Epoxy Thinner

Page 2 of 11

Date of Issue: 20/08/2021

### 2. HAZARDS IDENTIFICATION

#### Prevention Precautionary Statements:

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P103 - Read label before use

P202 - Do not handle until all safety precautions have been read and understood

P210 - Keep away from heat/sparks/open flames/hot surfaces – No smoking

P233+234 - Keep container tightly closed. Keep only in original container

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/light/...equipment

P242+243 - Use only non-sparking tools. Take precautionary measures against static discharge

P260 - Do not breathe dust/fume/gas/mist/vapour/spray

P262 - Do not get in eyes, on skin, or on clothing

P264 - Wash all exposed skin area thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace

P273 - Avoid release to the environment

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P285 - In case of inadequate ventilation wear respiratory protection

#### Response Precautionary Statements:

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P302+352 - IF ON SKIN: Wash with soap and water

P303+361+353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

P306+360 - IF ON CLOTHING: Rinse immediately contaminated clothing and skin with plenty of water before removing clothes

P312 - Call a POISON CENTRE or doctor/physician if you feel unwell.

P314 - Get medical advice/attention if you feel unwell.

P332+313 - If skin irritation occurs: Get medical advice/attention

P337+313 - If eye irritation persists get medical advice/attention

P362 - Take off contaminated clothing and wash before reuse.

P370+P378 - In case of fire: Use Foam, Dry Chemical Powder, Carbon Dioxide, Fine Water Spray or Fog (for large fires only) for extinction

P391 - Collect spillage

#### Storage Precautionary Statements:

P403+233+235: Store in a well-ventilated place. Keep container tightly closed. Keep cool

P405 - Store locked up

#### Disposal precautionary statements:

P501: Dispose of contents/container in accordance with local, regional, national and international regulations.

**Poison Schedule:** S6

## SAFETY DATA SHEET

Name: T181 GP Epoxy Thinner

Page: 3 of 11

Date of Issue: 20/08/2021

### 3. COMPOSITION/INFORMATION OF INGREDIENTS

| Component Name: | CAS Number: | Proportion %<br>Weight: |
|-----------------|-------------|-------------------------|
| Xylene          | 1330-20-7   | 60.0-90.0               |
| n-Butanol:      | 71-36-3     | 20.0-40.0               |

### 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or  
Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

#### Inhalation:

- Remove victim from exposure-avoid becoming a casualty. Remove all contaminated clothing and footwear.
- Allow patient to assume most comfortable position and keep warm.
- If inhalation of mists, fumes or vapour causes irritation to the nose, throat, or lungs, causing coughing, wheezing or impaired motor skills, remove patient to fresh air.
- Apply artificial respiration if not breathing.
- If symptoms persist, obtain medical advice.

#### Skin:

- Remove all contaminated clothing and footwear.
- Wash contaminated area thoroughly with soap and water as soon as reasonably practicable.
- For gross contamination immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble).
- For skin burns cover with a clean dry dressing if blistering occurs do not break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

#### Eyes:

- Immediately flush eyes with large amounts of water for at least 15 minutes.
- Method of irrigation; keep eyelids apart and away from eyes, routinely lift upper and lower eyelid away from eye while flushing with water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes.
- Removal of contact lenses should only be performed by skilled personnel.
- Transport to the nearest medical facility for additional treatment.

#### Swallowed:

- Do not induce vomiting, place person's face downwards, head lower than hips to prevent vomit entering lungs.
- Rinse mouth with water. Give water to drink.
- Avoid giving patient milk or oils.
- Observe patient carefully; withhold water if patient display signs of drowsiness or reduced awareness and possible unconsciousness.
- Seek medical advice.

#### First Aid Facilities:

- Ensure that eye wash bath and safety showers are readily accessible.

#### Advice to Doctor:

- Treat the patient symptomatically.

#### Other Information:

- For advice in an emergency, contact a Poisons Information Centre (Australia 13 11 26) or a doctor.

## SAFETY DATA SHEET

Name: T181 GP Epoxy Thinner

Page 4 of 11

Date of Issue: 20/08/2021

### 5. FIRE FIGHTING MEASURES

**Hazchem Code:** •3Y

**Fire & Explosion Hazard:**

- Liquid and vapour are highly flammable.
- Explosion hazard when exposed to heat or flame.
- Highly flammable liquid and vapour. Vapour/air mix may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.
- Will float and can be reignited on surface water.
- Containers may rupture violently when exposed to extreme heat.
- On combustion the following products may be produced, Carbon Dioxide, Carbon Monoxide, Soot and Toxic smoke.

**Fire Fighting:**

- Evacuate immediate area of non-emergency personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Wear full protective equipment including self-contained breathing apparatus.
- Fight fire from a safe distance, with adequate cover and safe fire escape exit.
- Use foam, dry chemical, or carbon dioxide extinguishers. Fine water spray may be used to cool containers to prevent vapour pressure build up.
- Prevent water runoff from entering storm water drains or waterways.

### 6. ACCIDENTAL RELEASE MEASURES

**Minor Spills:**

- Clean up all spills immediately.
- Eliminate all sources of ignition
- Wear full protective clothing (refer section 8)
- Avoid breathing vapour and contact with skin and eyes.
- Contain and absorb using earth, sand, vermiculite, or other absorbent material. DO NOT USE sawdust, this is flammable.
- Collect residues in a flammable waste container and dispose of according to local waste management regulations.
- Do not allow product to enter storm water drains or waterways.
- Immediately remove all contaminated clothing after containment.

**Major Spills:**

- Evacuate personnel from immediate area and move upwind.
- Alert Fire Brigade of location and nature of hazard
- Eliminate all sources of ignition
- Wear full protective clothing (refer section 8)
- If safe to do so eliminate source of spillage.
- Avoid breathing vapour and contact with skin and eyes.
- Prevent, by any means available, spillage from entering storm water drains or water ways.
- If possible, contain and absorb using earth, sand, vermiculite or other absorbent material. DO NOT USE sawdust, this is flammable.
- Use only anti-spark/ anti-static equipment to contain and remove spillage.
- Recoverable product should be collected into labeled flammable containers for recycling.
- Collect residues in a flammable waste container and dispose of according to local waste management regulations.
- Immediately remove all contaminated clothing after containment.

## SAFETY DATA SHEET

Name: T181 GP Epoxy Thinner

Page 5 of 11

Date of Issue: 20/08/2021

|                                |
|--------------------------------|
| <b>7. HANDLING AND STORAGE</b> |
|--------------------------------|

**Safe Storage:**

- Store product in accordance with Local State, or Territory Dangerous Goods Regulations.
- Keep containers closed when not in use.
- Store in a cool, dry, well-ventilated area out of direct sunlight, away from sources of heat or ignition.
- Do store in areas where vapour may be concentrated i.e., pits, basements, or unventilated storage area.
- For containers, or container linings use mild steel, stainless steel. Unsuitable Materials: Natural, butyl, neoprene, or nitrile rubbers.
- Do not store or load on the same vehicle as Class 1, Class 2.1, Class 2.3, Class 4.2, Class 5.1, Class 5.2 or Class 7 materials.

**Precautions for safe handling:**

- Do not smoke in storage/work area.
- Avoid skin and eye contact and breathing in vapour.
- All material handling equipment in work area must be flameproof.
- All nearby equipment should be earthed
- All potential sources of ignition must be eliminated from storage/work area.

|   |
|---|
| <b>8. EXPOSURE CONTROLS AND PERSONAL PROTECTION</b> |
|---|

**Occupational Exposure Limits:** No value assigned for this specific product by Safe Work Australia: Hazardous Substances Information System (HSIS). OEL for individual components reported.

**Concentration Cut-off Levels:**

A concentration cut-off level for a substance is the level (expressed as a percentage on a weight/weight basis for solids and liquids and a volume/volume basis for gases) at and above which that substance is classified as a hazardous substance. A mixture is classified as a hazardous substance if it contains at least one ingredient at a concentration equal to, or above, the lowest concentration cut-off level given for that ingredient.

Concentration cut-off levels refer to health hazards only and are not associated with the physicochemical or environmental hazards of a substance. The health effects of certain types of hazardous substances are regarded as additive. Due to additive effects, a mixture may be classified as hazardous even if all the individual substances in the mixture are present at levels below their respective cut offs.

| Chemical Name | CAS. No   | TWA (8hr) |       | STEL |       | Source  | Notices | %Weight |
|---------------|-----------|-----------|-------|------|-------|---------|---------|---------|
|               |           | ppm       | mg/m3 | ppm  | mg/m3 |         |         |         |
| Xylene        | 1330-20-7 | 80        | 350   | 150  | 655   | N/Eu; A |         | <90.00  |
| n-Butanol     | 71-36-3   | 50        | 152   |      |       |         | Sk      | <40.00  |

**Source:**

A Listed in the National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC: 1003(1995).

Eu Listed in the European Union's Annex I of the EEC Council Directive 67/548/EEC (as updated by EEC Council Directive 2001/59/EC).

NIOSH National Institute for Occupational Safety and Health.

NZWES New Zealand Workplace Exposure Standards and Biological Exposure Indices 7th edition

Sk Absorption through the skin may be a significant source of exposure.

(a) The value for inhalable dust containing no asbestos and less than 1.0% free silica.

ACGIH American Conference of Governmental Industrial Hygienists

## SAFETY DATA SHEET

Name: T181 GP Epoxy Thinner  
Page 6 of 11  
Date of Issue: 20/08/2021

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable.

Exposed individuals may be desensitised to product and are not reasonably expected to be warned, by smell, that exposure standard is being exceeded.

If the TWA concentration of ANY of the components is exceeded the individual is deemed to be over exposed.

If the directions for use on the Product Label/Safety Data Sheet are followed, exposure using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

**Biological Limit Values:**

**Biological Exposure Index (BEI):**

| Material | Determinant                   | Sampling Time | BEI              | Reference    |
|----------|-------------------------------|---------------|------------------|--------------|
| Xylene   | Methylhippuric acids in urine | End of shift  | 1.5 g/g creatine | ACGIH (2003) |

**Engineering Controls:** Use process enclosures, local exhaust ventilation or other engineering controls to maintain worker exposure to airborne contaminants below any recommended or statutory limits. Keep containers closed when not in use. Ensure exhaust air does not contaminate other workspaces.

Vapour heavier than air - Prevent vapours concentrating in work pits, tanks, or sumps. DO NOT enter confined spaces where vapour may have collected.

Ensure electrical equipment is in accordance with applicable regulations.

Equipment used to transfer product should be adequately earthed.

Ventilation equipment should be explosion/flame resistant.

Do not use near ignition sources.

**Personal Protection:** Avoid contact with skin and eyes. Wear suitable clothing such as impervious overalls, PVC, or Neoprene gloves, and safety goggles. Where workplace ventilation is assessed as inadequate and vapours/mists are generated, the use of an approved Half or Full-Face Respirator with Type A-P Filter complying with Australian Standards AS1715/1716 is recommended. Select a filter suitable for organic gases and vapours rated for; [boiling point > 65°C]. If working in confined spaces with inadequate ventilation, wear an air-fed full-face mask.



**Confined Space Application:**



**Flammability:** Highly flammable. Avoid heat and sources of ignition. Container should be earthed when pouring.

### 9. PHYSICAL AND CHEMICAL PROPERTIES:

**Appearance:** Colourless Liquid.

**Odour:** Aromatic

**Decomposition Temperature:** Not available

**Boiling Point (°C):** 136-145

**Solubility in Water:** Partial

**Solubility in Organic Solvents:** Soluble in hydrocarbons and acetone.

**Specific Gravity:** Not available

**pH:** Not available

**Volatile Component:** Not available

**Density:** 852 kg/m<sup>3</sup> (15°C) (typical)

**Flashpoint (°C):** 23.0-27.0 (Abel)

**Flammability:** Flammable.

## SAFETY DATA SHEET

Name: T181 GP Epoxy Thinner

Page 7 of 11

Date of Issue: 20/08/2021

|   |
|---|
| <b>9. PHYSICAL AND CHEMICAL PROPERTIES:</b> |
|---|

**Auto-ignition temperature (°C):** 432 - 530°C (ASTM E-659)  
**Explosion/Flammability Limits (% by Volume):** 1.0 - 7.1 in air  
**Solubility in other solvents (kg/m<sup>3</sup>):** Miscible

|                                      |
|--------------------------------------|
| <b>10. STABILITY AND REACTIVITY:</b> |
|--------------------------------------|

**Chemical stability:** Stable under normal conditions of storage and use.

**Do not store:** In areas of extreme heat generated by naked flame or heating element.  
 In the presence of incompatible materials. Refer Section 7.

**Reactivity and Stability:** Reacts with incompatible materials.

**Incompatible materials:** Strong oxidizing agents.

**Hazardous combustion:** Oxides of carbon and nitrogen, smoke and other toxic fumes.

**Possibility of hazardous reactions:** Reacts with incompatible materials.

|                                       |
|---------------------------------------|
| <b>11. TOXICOLOGICAL INFORMATION:</b> |
|---------------------------------------|

**Acute Toxicity: Refer Table 1 Section 16:**

| Chemical Name | Cas.No    | Result          | Species | Dose       | Exposure |
|---------------|-----------|-----------------|---------|------------|----------|
| Xylene        | 1330-20-7 | LD50 Oral       | Rat     | >2000mg/kg | 4 hours  |
|               |           | LD50 Dermal     | Rat     | >2000mg/kg |          |
|               |           | LC50 Inhalation | Rat     | >20mg/L    |          |
| n-Butanol     | 71-36-3   | LD50 Oral       | Rat     | 790mg/kg   | 4 hours  |
|               |           | LD50 Dermal     | Rabbit  | 3400mg/kg  |          |
|               |           | LC50 Inhalation | Rat     | 8000ppm    |          |

**Acute - Oral:** May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, oesophagus, and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.

**Acute - Eye:** Irritating to the eyes.

**Acute - Skin:** Irritating to the skin. Has a degreasing action on the skin. Repeated or prolonged skin contact may lead to contact dermatitis and toxic effects.

**Acute - Inhaled:** Vapour may be an irritant to mucous membranes and respiratory tract.

Inhalation of vapour can result in headaches, dizziness, and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and, if exposure is prolonged, unconsciousness. Harmful if inhaled.

## SAFETY DATA SHEET

Name: T181 GP Epoxy Thinner  
Page: 8 of 11  
Date of Issue: 20/08/2021

|                                       |
|---------------------------------------|
| <b>11. TOXICOLOGICAL INFORMATION:</b> |
|---------------------------------------|

**Respiratory sensitisation:** Not expected to be a respiratory sensitiser.  
**Skin Sensitisation:** Not expected to be a skin sensitiser.  
**Mutagenicity:** Not expected to be mutagenic.  
**Carcinogenicity:** Not considered to be a carcinogenic hazard.  
**Reproductive Toxicity:** Not considered to be toxic to reproduction. Causes foetotoxicity in animals at doses which are maternally toxic.  
**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**STOT-single exposure:** May cause respiratory irritation.  
**STOT-repeated exposure:** May cause damage to organs (hearing organs) through prolonged or repeated exposure.

|                                    |
|------------------------------------|
| <b>12. ECOLOGICAL INFORMATION:</b> |
|------------------------------------|

The available ecological data is given below.

**Aquatic Ecotoxicity**

| Chemical Name | Cas.No    | Species  | Result   | Method | Exposure |
|---------------|-----------|--|--|--------|----------|
| Xylene        | 1330-20-7 | Fish<br>Aquatic Crustacea<br>Algae   | 1<LC/EC/IC50<=10mg/L<br>1<LC/EC/IC50<=10mg/L<br>1<LC/EC/IC50<=10mg/L |        |          |
| n-Butanol     | 71-36-3   | Fish (Lepomis macrochirus)<br>Water Flea (Daphnia Magna)<br>Algae (Blue green) | LC50 - 100mg/L<br>EC50 - 312mg/L<br>EC50 - 185mg/L                   |        |          |

**Persistence and Biodegradability:** Readily biodegradable. Oxidises rapidly by photo-chemical reactions in air.  
**Bioaccumulative Potential:** Does not bioaccumulate significantly.  
**Mobility in Soil:** Floats on water. If product enters soil, it will be highly mobile and may contaminate groundwater.  
**Other Adverse Effects:** In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life.  
**Environmental Protection:** Prevent this material entering waterways, drains and sewers.

|                                    |
|------------------------------------|
| <b>13. DISPOSAL CONSIDERATION:</b> |
|------------------------------------|

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is use, See Section 8. "Exposure Controls and Personal Protection" of the SDS.

**Material Disposal:** Recover or recycle if possible. It is the responsibility of waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

**Container Disposal:** Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Refer to Section 7 before handling the product or containers. Residues may cause an explosion hazard if heat above flash point. Do not puncture, cut or weld uncleaned drums. Send to drum or meatal recyclers.

**Local Legislation:** Disposal should be in accordance with applicable regional, nation, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.



## SAFETY DATA SHEET

Name: T181 GP Epoxy Thinner  
Page: 9 of 11  
Date of Issue: 20/08/2021

### 14. TRANSPORT INFORMATION:

Classified as Dangerous Goods by criteria of the Australian Dangerous Goods Code (ADG Code) for transport by road or rail.



**Product Name:** T181 GP Epoxy Thinner  
**Other Names:** Paint Thinner  
**Manufacturer's Product Code:** T181  
**Hazard Label:** Flammable liquid  
**UN Number:** 1263  
**Packaging Group:** III  
**Dangerous Goods Class & Subsidiary Risk:** 3  
**Hazchem Code:** •3Y  
**Declaration for land shipment:** Flammable Liquid / Paint Related Material  
**Limited Quantity:** 5 litre

#### Air Transport IATA:

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA), Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

**Product Name:** T181 GP Epoxy Thinner  
**Hazard Label:** Flammable liquid  
**ICAO/IATA Class:** 3  
**Special Provisions:** None  
**UN No:** 1263  
**Packaging Group:** III  
**Packaging Instructions (passenger & cargo):** 355  
**Packaging Instructions (cargo only):** 366

#### Marine Transport:

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

**Product Name:** T181 GP Epoxy Thinner  
**UN No:** 1263  
**Class-primary:** 3 Flammable Liquid  
**Packing Group:** III  
**EMS:** F-E, S-D  
**Special Provisions:** None  
**IMDG Marine pollutant:** No

Do not load on the same vehicle as:

- Class 1: Explosives
- Class 2.1: Flammable Gases (if both are in bulk)
- Class 2.3: Toxic Gasses
- Class 4.2: Spontaneously Combustible Substances
- Class 5.1: Oxidising Agents
- Class 5.2: Organic Peroxides
- Class 7: Radioactive Substances

## SAFETY DATA SHEET

Name: T181 GP Epoxy Thinner  
Page: 10 of 11  
Date of Issue: 20/08/2021

### 15. REGULATORY INFORMATION

**Poison Schedule:** S6

#### Individual components of T181 GP Epoxy Thinner on regulatory listings:

Xylene: **CAS No: 1330-20-7:** AICS, DSL, ENCS, IECSC, ISHL, KECL, PICCS, NZIoC, IRAC.  
n-Butanol: **CAS No: 71-36-3:** AICS, DSL, ENCS, IECSC, ISHL, KECL, NZIoC, PICCS

#### IRAC GROUP CLASSIFICATION:

- Group 1 Carcinogenic to humans:
- Group 2A Probably carcinogenic to humans:
- Group 2B Possibly carcinogenic to humans:
- Group 3 Not classifiable as to its carcinogenicity to humans: CAS No: 1330-20-7
- Group 4 Probably not carcinogenic to humans:

#### REGULATORY LISTINGS:

**SUSDP:** Standard for the Uniform Scheduling of Drugs and Poisons

**HSIS:** Safe work Australia Hazardous Substances Information System

**NPI:** The National Pollutant Inventory

**OECD:** Organisation for Economic Co-operation and Development.

**AICS:** Australian Inventory of Chemical Substances

**EINECS:** European Inventory of Existing Commercial Chemical Substances

**TSCA:** US Toxic Substances Control Act

**DSL:** Canadian Domestic Substances List.

**IRAC:** International Agency for Research on Cancer

**PICCS:** Philippines Inventory of Chemicals and Chemical Substances

**KECL:** Korea Existing Chemicals List

**ENCS:** Japan Existing and New Chemical Substances

**REACH:** Registration, Evaluation, Authorisation and Restriction of Chemicals

**DSL/NDL:** Canadian Domestic Substances List/Non-Domestic Substance List

**NZIoC:** New Zealand Inventory of Chemicals

**IECSC:** Chinese Chemical Inventory of Existing Chemical Substances

**KECI:** Korea Existing Chemicals Inventory

**HSNO:** New Zealand Hazardous Substances and New Organisms Act

**ISHL:** Japan Industrial Safety and Health Law

**NICNAS:** National Industrial Chemicals Notification and Assessment Scheme

**MITI:** Japanese Handbook of Existing and New Chemical Substances

**IVN (CN):**

### 16. OTHER INFORMATION:

**CAS No:** CAS Registry Number is a unique numeric identifier that designates only one substance. It has no chemical significance.

**ACGIH:** American Conference of Industrial Hygienists.

**TWA:** Exposure standard-time weighted average; the average airborne concentration of a particle substance when calculated over a normal eight hour working day, for a five-day week.

**STEL:** Short-term exposure limit (STEL) is the acceptable exposure limit to a toxic or an irritant substance over a short period of time (time-weighted average), usually 15 minutes. STEL is the maximum concentration of a chemical to which workers may be exposed continuously for a short period of time without any danger to health, safety, or work efficiency.

**ppm:** Parts of vapour or gas per million parts of contaminated air by volume.

**mg/m<sup>3</sup>:** Milligrams of substance per cubic metre of air at 25°C and one atmosphere pressure. When entry is in this column only the value is exact; when listed with a ppm value, it is approximate.

**LD50:** Lethal Dosage represents the individual dose required to kill 50 percent of a population of test animals.

## SAFETY DATA SHEET

Name: T181 GP Epoxy Thinner  
Page: 11 of 11  
Date of Issue: 20/08/2021

|            |                           |
|------------|---------------------------|
| <b>16.</b> | <b>OTHER INFORMATION:</b> |
|------------|---------------------------|

**LC50:** Lethal Concentrations of the chemical in air that kills 50% of the test animals during the observation period (traditional 4 hours). It can also mean the concentration of a chemical in water.

**EC50:** The Median Effective Concentration is the statistically derived concentration of a substance in an environmental medium expected to produce a certain effect in 50% of test organisms in each population under a defined set of conditions.

**IC50:** Half Maximal Inhibitory Concentration is a measure of the effectiveness of a substance in inhibiting a specific biological or biochemical function. This quantitative measure indicates how much of a particular drug or other substance is needed to inhibit a given biological process (or component of a process, i.e., an enzyme, cell, cell receptor or microorganism) by half.

**LDL0:** Lethal Dose Low, lowest dose of a substance reported to have caused death in humans or animals.

**NOEC/NOEL:** No Observable Effect Concentration/Level

**Toxicity classification: Table 1**

| <b>Toxicity Classes: Hodge and Sterner Scale</b> |                       |                                    |   |  |                                     |
|--|-----------------------|------------------------------------|---|--|-------------------------------------|
|  |                       | <b>Route of Administration</b>     |   |  |                                     |
| <b>Toxicity Rating</b>                           | <b>Common Term</b>    | <b>Oral LD50</b>                   | <b>Inhalation LC50</b>                    | <b>Dermal LD<sub>50</sub></b>                        | <b>Probable Lethal Dose for Man</b> |
|  |                       | <b>(single dose to rats) mg/kg</b> | <b>(exposure of rats for 4 hours) ppm</b> | <b>(single application to skin of rabbits) mg/kg</b> |                                     |
| 1  | Extremely Toxic       | 1 or less                          | 10 or less                                | 5 or less  | 1 grain (a taste, a drop)           |
| 2  | Highly Toxic          | 1 to 50                            | 10 to 100                                 | 5 to 43  | 4 ml (1 tsp)                        |
| 3  | Moderately Toxic      | 50 to 500                          | 100 to 1000                               | 44 to 340  | 30 ml (1 fl. oz.)                   |
| 4  | Slightly Toxic        | 500 to 5000                        | 1000 to 10000                             | 350 to 2810  | 600 ml (1 pint)                     |
| 5  | Practically Non-Toxic | 5000 to 15000                      | 10000 to 100000                           | 2820 to 22590  | 1 litre (or 1 quart)                |
| 6  | Relatively Harmless   | 15000 or more                      | 100000 or more                            | 22600 or more  | 1 litre (or 1 quart)                |

**Toxicity classification: Table 2**

|            |             |                    |
|------------|-------------|--------------------|
| LC/EC/IC50 | < 1 mg/l    | very high toxicity |
| LC/EC/IC50 | 1-10 mg/l   | high toxicity      |
| LC/EC/IC50 | 10-100 mg/l | moderate toxicity  |
| LC/EC/IC50 | >100 mg/l   | low toxicity       |

**SDS Effective Date:** 20/08/2021

**SDS Distribution:** The information in this document should be made available to all who may handle the product.

| <b>CONTACT POINT</b>     |                 |                       |
|--------------------------|-----------------|-----------------------|
| <b>Technical Manager</b> | - Working hours | <b>(02) 9688-1999</b> |
|                          | - After hours   | <b>0419 260 572</b>   |

Although this information is presented in good faith and compiled from various sources believed to be accurate, Lacnam Paints make no representations or warranty as to the completeness or accuracy thereof. As the product's performance and suitability depends on various factors, the purchasers of our products should determine for themselves whether the product is suitable for their particular use.

|  |
|--|
| <b>Hazardous according to criteria of Australian Safety Compensation Council</b> |
|--|