



Sydney Head Office:
Phone: 02 9688 1999
Fax: 02 9896 1606
78 – 80 Mandoon Road
Girraween, 2145, NSW
sales@lacnam.com.au

Newcastle Branch Office:
Phone: 02 4967 1055
Fax: 02 4967 1066
Unit1, 11 Spit Island Close
Steel River Industrial Estate
Mayfield West, NSW, 2304

Brisbane Branch Office:
Phone: 07 3271 3323
Fax: 07 3271 3448
Warehouse C, 69 Cobalt St
(enter from Mica St)
Carole Park, QLD,4300

AEROSOL CONTAINERS 405

LACNAM AEROSOLS are available (Minimum order 12 cans) in single pack finish including primers and topcoats.

They are ideal for touch-up work and for those small, difficult to get at areas.

They are available in 450 gram containers.

DIRECTIONS FOR USE

For interior and exterior use on machinery, gates, wrought iron, in fact anywhere that a quality finish is required. Touch dry in two hours.

SURFACE PREPARATION

Surface must be clean of dust, wax, grease and rust. All metal recommended to be primed with metal primer.

SHAKE CAN THOROUGHLY for at least one minute to mix the paint to ensure an even result.

SPRAY APPLICATION

Hold can approximately 30cm from surface. Depress valve head and spray with smooth even strokes horizontally then vertically, applying several light coats rather than one heavy coat to achieve the best results.

AFTER USE

Turn can upside down and spray until jet clears. Any overspray may be cleaned up while still wet with turps.

CAUTION: HIGHLY FLAMMABLE

Do not use near fire or flame. Do not puncture or incinerate can even when empty. Do not store above 50 degrees C.

Keep spray away from eyes.

KEEP OUT OF REACH OF CHILDREN

WARNING: Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

PROPELLANT: HYDROCARBON